
Subject: Re: [PATCH 2/11 net-2.6.26] [DCCP]: Replace socket with sock for reset sending.

Posted by [Arnaldo Carvalho de M](#) on Fri, 28 Mar 2008 14:39:59 GMT

[View Forum Message](#) <> [Reply to Message](#)

Em Fri, Mar 28, 2008 at 12:08:49PM +0300, Denis V. Lunev escreveu:

> Replace dccp_v(4|6)_ctl_socket with sock to unify a code with TCP/ICMP.

>

> Signed-off-by: Denis V. Lunev <den@openvz.org>

> ---

> net/dccp/ipv4.c | 16 ++++++-----

> net/dccp/ipv6.c | 10 +++++----

> 2 files changed, 15 insertions(+), 11 deletions(-)

>

> diff --git a/net/dccp/ipv4.c b/net/dccp/ipv4.c

> index 4ca8b0c..79a9a4a 100644

> --- a/net/dccp/ipv4.c

> +++ b/net/dccp/ipv4.c

> @@ -36,7 +36,7 @@

> * the Out-of-the-blue (OOTB) packets. A control sock will be created

> * for this socket at the initialization time.

> */

> -static struct socket *dccp_v4_ctl_socket;

> +static struct sock *dccp_v4_ctl_sk;

>

> int dccp_v4_connect(struct sock *sk, struct sockaddr *uaddr, int addr_len)

> {

> @@ -514,11 +514,11 @@ static void dccp_v4_ctl_send_reset(struct sock *sk, struct sk_buff
*rxskb)

> if (rxskb->rtable->rt_type != RTN_LOCAL)

> return;

>

> - dst = dccp_v4_route_skb(dccp_v4_ctl_socket->sk, rxskb);

> + dst = dccp_v4_route_skb(dccp_v4_ctl_sk, rxskb);

> if (dst == NULL)

> return;

>

> - skb = dccp_ctl_make_reset(dccp_v4_ctl_socket, rxskb);

> + skb = dccp_ctl_make_reset(dccp_v4_ctl_sk->sk_socket, rxskb);

Why not make dccp_ctl_make_reset receive a struct sock too? It only uses
ctl->sk anyway. But I guess that can be on a follow-up patch, could you
that?

Thanks,

- Arnaldo

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
