
Subject: [PATCH 12/13 net-2.6.26] [NETNS]: Create tcp control socket in the each namespace.

Posted by [den](#) on Mon, 31 Mar 2008 13:16:52 GMT

[View Forum Message](#) <> [Reply to Message](#)

Signed-off-by: Denis V. Lunev <den@openvz.org>

```
include/net/netns/ipv4.h |  1 +
net/ipv4/tcp_ipv4.c    | 21 ++++++=====
2 files changed, 20 insertions(+), 2 deletions(-)
```

```
diff --git a/include/net/netns/ipv4.h b/include/net/netns/ipv4.h
```

```
index af685f7..34ee348 100644
```

```
--- a/include/net/netns/ipv4.h
```

```
+++ b/include/net/netns/ipv4.h
```

```
@@ -28,6 +28,7 @@ struct netns_ipv4 {
```

```
    struct sock *fibnl;
```

```
    struct sock **icmp_sk;
```

```
+   struct sock *tcp_sock;
```

```
    struct netns_frags frags;
```

```
#ifdef CONFIG_NETFILTER
```

```
diff --git a/net/ipv4/tcp_ipv4.c b/net/ipv4/tcp_ipv4.c
```

```
index dc8c3dc..1d4a77a 100644
```

```
--- a/net/ipv4/tcp_ipv4.c
```

```
+++ b/net/ipv4/tcp_ipv4.c
```

```
@@ -2488,11 +2488,28 @@ struct proto tcp_prot = {
```

```
#endif
```

```
};
```

```
+
```

```
+static int __net_init tcp_sk_init(struct net *net)
```

```
{
```

```
+   return inet_ctl_sock_create(&net->ipv4.tcp_sock,
```

```
+     PF_INET, SOCK_RAW, IPPROTO_TCP, net);
```

```
}
```

```
+
```

```
+static void __net_exit tcp_sk_exit(struct net *net)
```

```
{
```

```
+   inet_ctl_sock_destroy(net->ipv4.tcp_sock);
```

```
}
```

```
+
```

```
+static struct pernet_operations __net_initdata tcp_sk_ops = {
```

```
+   .init = tcp_sk_init,
```

```
+   .exit = tcp_sk_exit,
```

```
+};
```

```
+
```

```
void __init tcp_v4_init(void)
{
- if (inet_ctl_sock_create(&tcp_sock, PF_INET, SOCK_RAW,
-   IPPROTO_TCP, &init_net) < 0)
+ if (register_pernet_device(&tcp_sk_ops))
  panic("Failed to create the TCP control socket.\n");
+ tcp_sock = init_net.ipv4.tcp_sock;
}
```

EXPORT_SYMBOL(ipv4_specific);

--
1.5.3.rc5

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
