
Subject: [RFC][patch 11/11][CFQ-cgroup] entry/remove active cfq_data
Posted by Satoshi UCHIDA on Tue, 01 Apr 2008 09:42:35 GMT

[View Forum Message](#) <> [Reply to Message](#)

This patch controls whether cfq_data is active or not.

When cfq_data is not active and active cfq_queue is inserted into cfq_data,
cfq_data is activated.

When cfq_data is active and active cfq_queue is not exist,
cfq_data is deactivated.

The new cfq optional operations:

The "cfq_add_cfqq_opt_fn" defines a function that runs an additional process
when active queue is inserted into cfq_data.

The "cfq_del_cfqq_opt_fn" defines a function that runs an additional process
when active queue is removed in cfq_data.

Signed-off-by: Satoshi UCHIDA <uchida@ap.jp.nec.com>

```
diff --git a/block/cfq-cgroup.c b/block/cfq-cgroup.c
index f040c98..46f3635 100644
--- a/block/cfq-cgroup.c
+++ b/block/cfq-cgroup.c
@@ -741,6 +741,32 @@ static int cfq_cgroup_active_data_check(struct cfq_data *cfqd)
    return (cfqd->cfqmd->active_data == cfqd);
}

+static void cfq_cgroup_add_cfqd_rr(struct cfq_data *cfqd)
+{
+ if (!cfq_cfqd_on_rr(cfqd)) {
+   cfq_mark_cfqd_on_rr(cfqd);
+   cfqd->cfqmd->busy_data++;
+
+   cfq_cgroup_service_tree_add(cfqd, 0);
+ }
+}
+
+
+static void cfq_cgroup_del_cfqd_rr(struct cfq_data *cfqd)
+{
+ if (RB_EMPTY_ROOT(&cfqd->service_tree.rb)) {
+   struct cfq_meta_data *cfqdd = cfqd->cfqmd;
+   BUG_ON(!cfq_cfqd_on_rr(cfqd));
+   cfq_clear_cfqd_on_rr(cfqd);
+   if (!RB_EMPTY_NODE(&cfqd->rb_node)) {
+     cfq_rb_erase(&cfqd->rb_node,
+                  &cfqdd->service_tree);
+   }
+ }
```

```

+ BUG_ON(!cfqdd->busy_data);
+ cfqdd->busy_data--;
+ }
+
+ struct cfq_ops opt = {
+ .cfq_init_queue_fn = __cfq_cgroup_init_queue,
+ .cfq_exit_queue_fn = __cfq_cgroup_exit_data,
@@ -749,4 +775,6 @@ struct cfq_ops opt = {
+ .cfq_completed_request_after_fn = cfq_cgroup_completed_request_after,
+ .cfq_empty_fn = cfq_cgroup_queue_empty,
+ .cfq_active_check_fn = cfq_cgroup_active_data_check,
+ .cfq_add_cfqq_opt_fn = cfq_cgroup_add_cfqd_rr,
+ .cfq_del_cfqq_opt_fn = cfq_cgroup_del_cfqd_rr,
};

diff --git a/block/cfq-iosched.c b/block/cfq-iosched.c
index 505e425..8f5227f 100644
--- a/block/cfq-iosched.c
+++ b/block/cfq-iosched.c
@@ -492,6 +492,9 @@ static void cfq_add_cfqq_rr(struct cfq_data *cfqd, struct cfq_queue *cfqq)
    cfqd->busy_queues++;
}

cfq_resort_rr_list(cfqd, cfqq);
+
+ if (opt.cfq_add_cfqq_opt_fn)
+ opt.cfq_add_cfqq_opt_fn(cfqd);
}

/*
@@ -508,6 +511,9 @@ static void cfq_del_cfqq_rr(struct cfq_data *cfqd, struct cfq_queue *cfqq)

BUG_ON(!cfqd->busy_queues);
cfqd->busy_queues--;
+
+ if (opt.cfq_del_cfqq_opt_fn)
+ opt.cfq_del_cfqq_opt_fn(cfqd);
}

/*
diff --git a/include/linux/cfq-iosched.h b/include/linux/cfq-iosched.h
index 63d2545..ed35050 100644
--- a/include/linux/cfq-iosched.h
+++ b/include/linux/cfq-iosched.h
@@ -161,6 +161,8 @@ typedef int (cfq_dispatch_requests_fn)(struct cfq_data *, int);
typedef int (cfq_completed_request_after_fn)(struct cfq_data *);
typedef int (cfq_active_check_fn)(struct cfq_data *);
typedef int (cfq_empty_fn)(struct cfq_data *);
+typedef void (cfq_add_cfqq_opt_fn)(struct cfq_data *);

```

```
+typedef void (cfq_del_cfqq_opt_fn)(struct cfq_data *);  
  
struct cfq_ops  
{  
@@ -171,6 +173,8 @@ struct cfq_ops  
    cfq_completed_request_after_fn *cfq_completed_request_after_fn;  
    cfq_active_check_fn *cfq_active_check_fn;  
    cfq_empty_fn *cfq_empty_fn;  
+   cfq_add_cfqq_opt_fn *cfq_add_cfqq_opt_fn;  
+   cfq_del_cfqq_opt_fn *cfq_del_cfqq_opt_fn;  
};  
  
extern struct cfq_ops opt;
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
