

---

Subject: [PATCH -mm 0/3] cgroup: use hash table for css\_set  
Posted by [Li Zefan](#) on Thu, 03 Apr 2008 05:52:33 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

(rebase on 2.6.25-rc8-mm1)

When we attach a process to a different cgroup, the css\_set linked-list will be run through to find a suitable existing css\_set to use. This patch set uses a hash table for better performance.

As we add the hash table, we can totally remove the css\_set linked-list. When we have to run through the linked-list, we can run through the hash table instead.

I tested the following benchmarks:

For N in 1, 5, 10, 50, 100, 500, 1000, create N cgroups with one sleeping task in each, and then move an additional task through each cgroup in turn.

Here is a test result:

N Loop orig - Time(s) hash - Time(s)

-----  
1 10000 1.201231728 1.196311177  
5 2000 1.065743872 1.040566424  
10 1000 0.991054735 0.986876440  
50 200 0.976554203 0.969608733  
100 100 0.998504680 0.969218270  
500 20 1.157347764 0.962602963  
1000 10 1.619521852 1.085140172

Regards,  
Li Zefan

---

Containers mailing list  
[Containers@lists.linux-foundation.org](mailto:Containers@lists.linux-foundation.org)  
<https://lists.linux-foundation.org/mailman/listinfo/containers>

---