
Subject: [PATCH -mm 3/3] cgroup: remove the css_set linked-list
Posted by [Li Zefan](#) on Thu, 03 Apr 2008 05:53:15 GMT
[View Forum Message](#) <> [Reply to Message](#)

Now we can run through the hash table instead of running through the linked-list.

Signed-off-by: Li Zefan <lizf@cn.fujitsu.com>

include/linux/cgroup.h | 6 -----
kernel/cgroup.c | 40 ++++++++-----
2 files changed, 20 insertions(+), 26 deletions(-)

diff --git a/include/linux/cgroup.h b/include/linux/cgroup.h
index f585b7c..d58a958 100644

--- a/include/linux/cgroup.h
+++ b/include/linux/cgroup.h
@@ -150,12 +150,6 @@ struct css_set {
 struct kref ref;

/*
- * List running through all cgroup groups. Protected by
- * css_set_lock
- */
- struct list_head list;
-
- /*
 * List running through all cgroup groups in the same hash
 * slot. Protected by css_set_lock
 */

diff --git a/kernel/cgroup.c b/kernel/cgroup.c
index 250e28e..9e7cf16 100644

--- a/kernel/cgroup.c
+++ b/kernel/cgroup.c
@@ -241,7 +241,6 @@ static void unlink_css_set(struct css_set *cg)
{
 write_lock(&css_set_lock);
 hlist_del(&cg->hlist);
- list_del(&cg->list);
 css_set_count--;
 while (!list_empty(&cg->cg_links)) {
 struct cg_cgroup_link *link;
@@ -476,8 +475,6 @@ static struct css_set *find_css_set(

 BUG_ON(!list_empty(&tmp_cg_links));

- /* Link this cgroup group into the list */
- list_add(&res->list, &init_css_set.list);

```

css_set_count++;

/* Add this cgroup group to the hash table */
@@ -962,7 +959,7 @@ static int cgroup_get_sb(struct file_system_type *fs_type,
    int ret = 0;
    struct super_block *sb;
    struct cgroupfs_root *root;
- struct list_head tmp_cg_links, *l;
+ struct list_head tmp_cg_links;
    INIT_LIST_HEAD(&tmp_cg_links);

/* First find the desired set of subsystems */
@@ -1004,6 +1001,7 @@ static int cgroup_get_sb(struct file_system_type *fs_type,
/* New superblock */
    struct cgroup *cgrp = &root->top_cgroup;
    struct inode *inode;
+ int i;

    BUG_ON(sb->s_root != NULL);

@@ -1048,22 +1046,25 @@ static int cgroup_get_sb(struct file_system_type *fs_type,
/* Link the top cgroup in this hierarchy into all
 * the css_set objects */
    write_lock(&css_set_lock);
- l = &init_css_set.list;
- do {
+ for (i = 0; i < CSS_SET_TABLE_SIZE; i++) {
+ struct hlist_head *hhead = &css_set_table[i];
+ struct hlist_node *node;
    struct css_set *cg;
- struct cg_cgroup_link *link;
- cg = list_entry(l, struct css_set, list);
- BUG_ON(list_empty(&tmp_cg_links));
- link = list_entry(tmp_cg_links.next,
- struct cg_cgroup_link,
- cgrp_link_list);
- list_del(&link->cgrp_link_list);
- link->cg = cg;
- list_add(&link->cgrp_link_list,
- &root->top_cgroup.css_sets);
- list_add(&link->cg_link_list, &cg->cg_links);
- l = l->next;
- } while (l != &init_css_set.list);
+
+ hlist_for_each_entry(cg, node, hhead, hlist) {
+ struct cg_cgroup_link *link;
+
+ BUG_ON(list_empty(&tmp_cg_links));

```

```

+ link = list_entry(tmp_cg_links.next,
+   struct cg_cgroup_link,
+   cgrp_link_list);
+ list_del(&link->cgrp_link_list);
+ link->cg = cg;
+ list_add(&link->cgrp_link_list,
+   &root->top_cgroup.css_sets);
+ list_add(&link->cg_link_list, &cg->cg_links);
+ }
+ }
  write_unlock(&css_set_lock);

  free_cg_links(&tmp_cg_links);
@@ -2508,7 +2509,6 @@ int __init cgroup_init_early(void)
  int i;
  kref_init(&init_css_set.ref);
  kref_get(&init_css_set.ref);
- INIT_LIST_HEAD(&init_css_set.list);
  INIT_LIST_HEAD(&init_css_set.cg_links);
  INIT_LIST_HEAD(&init_css_set.tasks);
  INIT_HLIST_NODE(&init_css_set.hlist);
--

```

1.5.4.rc3

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
