
Subject: [PATCH 6/8 net-2.6.26] [NETNS]: Add netns refcnt debug for dst ops.

Posted by [den](#) on Tue, 15 Apr 2008 12:37:53 GMT

[View Forum Message](#) <> [Reply to Message](#)

Signed-off-by: Denis V. Lunev <den@openvz.org>

```
net/ipv6/route.c | 4 +++-
1 files changed, 3 insertions(+), 1 deletions(-)
```

```
diff --git a/net/ipv6/route.c b/net/ipv6/route.c
```

```
index 6293cb9..210a079 100644
```

```
--- a/net/ipv6/route.c
```

```
+++ b/net/ipv6/route.c
```

```
@@ -2622,7 +2622,7 @@ static int ip6_route_net_init(struct net *net)
    GFP_KERNEL);
```

```
    if (!net->ipv6.ip6_dst_ops)
        goto out;
```

```
    - net->ipv6.ip6_dst_ops->dst_net = net;
```

```
    + net->ipv6.ip6_dst_ops->dst_net = hold_net(net);
```

```
    net->ipv6.ip6_null_entry = kmemdup(&ip6_null_entry_template,
        sizeof(*net->ipv6.ip6_null_entry),
```

```
@@ -2669,6 +2669,7 @@ out:
```

```
    return ret;
```

```
out_ip6_dst_ops:
```

```
+ release_net(net->ipv6.ip6_dst_ops->dst_net);
```

```
    kfree(net->ipv6.ip6_dst_ops);
```

```
    goto out;
```

```
}
```

```
@@ -2684,6 +2685,7 @@ static void ip6_route_net_exit(struct net *net)
```

```
    kfree(net->ipv6.ip6_prohibit_entry);
```

```
    kfree(net->ipv6.ip6_blk_hole_entry);
```

```
#endif
```

```
+ release_net(net->ipv6.ip6_dst_ops->dst_net);
```

```
    kfree(net->ipv6.ip6_dst_ops);
```

```
}
```

```
--
```

```
1.5.3.rc5
```

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
