

---

Subject: Re: Pb with multiple identical nfs mount dir in different VEs

Posted by [maratrus](#) on Wed, 30 Apr 2008 08:07:22 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hi,

I've suspected that something is not quite clear with ubuntu "ifdown\*" utilities.  
But the fact is that in redhat based OS ifdown is a simple script so it's easy to investigate it:  
it calls appropriate script in /etc/sysconfig/network-scripts/.  
And the only thing I've found there is:

```
if [ -n "$VLAN" -a -x /sbin/vconfig ]; then
    # 802.1q VLAN
    if echo ${DEVICE} | LANG=C egrep -v '(:)' | LANG=C egrep -q
'(eth|bond)[0-9][0-9]*\.[0-9][0-9]?[0-9]?[0-9]? \
    || echo ${DEVICE} | LANG=C egrep -q 'vlan[0-9][0-9]?[0-9]?[0-9]?' ; then
        [ -f /proc/net/vlan/${DEVICE} ] && {
            /sbin/vconfig rem ${DEVICE}
        }
    fi
fi
```

So,

1. If it's possible we can investigate src files of appropriate utilities in ubuntu OS.
- 2.

Quote:

```
strace ifdown eth1.35 > /tmp/ifdown.eth1.35.trace 2>&1
```

ifdown can generate another process so could you possible try to it in the following way:

```
strace -fF -o out.txt ifdown eth1.35
```

Thank You!

---