

---

Subject: [PATCH 10/11] netns: Enable tagging for net\_class directories in sysfs

Posted by [Benjamin Thery](#) on Wed, 18 Jun 2008 17:09:09 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

net: Enable tagging for net\_class directories in sysfs

The problem. Network devices show up in sysfs and with the network namespace active multiple devices with the same name can show up in the same directory, ouch!

To avoid that problem and allow existing applications in network namespaces to see the same interface that is currently presented in sysfs, this patch enables the tagging directory support in sysfs.

By using the network namespace pointers as tags to separate out the sysfs directory entries we ensure that we don't have conflicts in the directories and applications only see a limited set of the network devices.

Signed-off-by: Eric W. Biederman <[ebiederm@xmission.com](mailto:ebiederm@xmission.com)>

Signed-off-by: Benjamin Thery <[benjamin.thery@bull.net](mailto:benjamin.thery@bull.net)>

---

```
fs/sysfs/mount.c    |  8 ++++++++
include/linux/sysfs.h |  2 ++
net/Kconfig         |  2 ++
net/core/net-sysfs.c | 45 ++++++++++++++++++++++++++++++++
4 files changed, 56 insertions(+), 1 deletion(-)
```

Index: linux-mm/fs/sysfs/mount.c

=====

```
--- linux-mm.orig/fs/sysfs/mount.c
+++ linux-mm/fs/sysfs/mount.c
@@ -16,6 +16,8 @@
#include <linux/mount.h>
#include <linux/pagemap.h>
#include <linux/init.h>
+#include <linux/nsproxy.h>
+#include <net/net_namespace.h>

#include "sysfs.h"

@@ -78,6 +80,7 @@
 static int sysfs_fill_super(struct super
 root->d_sb = sb;
 sb->s_root = root;
 sb->s_fs_info = info;
+info->tag.net_ns = hold_net(current->nsproxy->net_ns);
 return 0;
```

```
out_err:  
@@ -95,6 +98,9 @@ static int sysfs_test_super(struct super  
 struct sysfs_super_info *info = sysfs_info(sb);  
 int found = 1;  
  
+ if (task->nsproxy->net_ns != info->tag.net_ns)  
+ found = 0;  
+  
 return found;  
}
```

```
@@ -131,6 +137,8 @@ static void sysfs_kill_sb(struct super_b  
 struct sysfs_super_info *info = sysfs_info(sb);
```

```
kill_anon_super(sb);  
+ if (info->tag.net_ns)  
+ release_net(info->tag.net_ns);  
kfree(info);  
}
```

Index: linux-mm/include/linux/sysfs.h

```
=====--- linux-mm.orig/include/linux/sysfs.h  
+++ linux-mm/include/linux/sysfs.h  
@@ -19,6 +19,7 @@
```

```
struct kobject;  
struct module;  
+struct net;
```

```
extern int kobject_set_name(struct kobject *kobj, const char *name, ...)  
    __attribute__((format(printhf, 2, 3)));  
@@ -81,6 +82,7 @@ struct sysfs_ops {  
};
```

```
struct sysfs_tag_info {  
+ struct net *net_ns;  
};
```

```
struct sysfs_tagged_dir_operations {
```

Index: linux-mm/net/Kconfig

```
=====--- linux-mm.orig/net/Kconfig  
+++ linux-mm/net/Kconfig  
@@ -30,7 +30,7 @@ menu "Networking options"  
config NET_NS  
    bool "Network namespace support"  
    default n
```

- depends on EXPERIMENTAL && !SYSFS && NAMESPACES  
+ depends on EXPERIMENTAL && NAMESPACES  
  help  
    Allow user space to create what appear to be multiple instances  
    of the network stack.

Index: linux-mm/net/core/net-sysfs.c

```
=====
--- linux-mm.orig/net/core/net-sysfs.c
+++ linux-mm/net/core/net-sysfs.c
@@ -13,7 +13,9 @@
#include <linux/kernel.h>
#include <linux/netdevice.h>
#include <linux/if_arp.h>
+#include <linux/nsproxy.h>
#include <net/sock.h>
+#include <net/net_namespace.h>
#include <linux/rtnetlink.h>
#include <linux/wireless.h>
#include <net/iw_handler.h>
@@ -385,6 +387,28 @@ static struct attribute_group wireless_g
};

#endif

+/*
+ * sysfs: allow the net namespace to go away while sysfs is still mounted.
+ */
+static void net_sysfs_net_exit_cb(struct sysfs_tag_info *tag_info, void *data)
+{
+ struct net *net = (struct net *)data;
+
+ if (tag_info->net_ns != net)
+ return;
+ release_net(tag_info->net_ns);
+ tag_info->net_ns = NULL;
+}
+
+void net_sysfs_net_exit(struct net *net)
+{
+ sysfs_ns_exit(net_sysfs_net_exit_cb, net);
+}
+
+static struct pernet_operations net_sysfs_ops = {
+ .exit = net_sysfs_net_exit,
+};
+
#endif /* CONFIG_SYSFS */

#ifndef CONFIG_HOTPLUG
```

```

@@ -421,6 +445,23 @@ static void netdev_release(struct device
    kfree((char *)dev - dev->padded);
}

+static const void *net_sb_tag(struct sysfs_tag_info *info)
+{
+ return info->net_ns;
+}
+
+static const void *net_kobject_tag(struct kobject *kobj)
+{
+ struct net_device *dev;
+ dev = container_of(kobj, struct net_device, dev.kobj);
+ return dev_net(dev);
+}
+
+static const struct sysfs_tagged_dir_operations net_tagged_dir_operations = {
+ .sb_tag = net_sb_tag,
+ .kobject_tag = net_kobject_tag,
+};
+
static struct class net_class = {
    .name = "net",
    .dev_release = netdev_release,
@@ -430,6 +471,7 @@ static struct class net_class = {
#define CONFIG_HOTPLUG
    .dev_uevent = netdev_uevent,
#endif
+ .tag_ops = &net_tagged_dir_operations,
};

/* Delete sysfs entries but hold kobject reference until after all
@@ -475,5 +517,8 @@ void netdev_initialize_kobject(struct ne

int netdev_kobject_init(void)
{
#ifndef CONFIG_SYSFS
+ register_pernet_subsys(&net_sysfs_ops);
#endif
    return class_register(&net_class);
}

--
```

---

Containers mailing list  
 Containers@lists.linux-foundation.org  
<https://lists.linux-foundation.org/mailman/listinfo/containers>