

---

Subject: Re: [RFC][PATCH][cryo] Save/restore state of unnamed pipes  
Posted by [Matt Helsley](#) on Fri, 20 Jun 2008 02:48:19 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

On Thu, 2008-06-19 at 18:54 -0700, sukadev@us.ibm.com wrote:

> Matt Helsley [matthlrc@us.ibm.com] wrote:

<snip>

```
> | if (pipefds[0] != restarted_read_fd) {  
> |     dup2(pipefds[1], restarted_write_fd);  
> |     close(pipefds[1]);  
> | }  
>  
> Shouldn't the last if be  
>  
> if (pipefds[1] != restarted_wrted_fd) ?  
>  
> (otherwise it would break if pipefds[0] = 11 and pipefds[1] = 200)
```

Argh, copy-paste error. You are correct.

```
> I came up with something similar, but with an extra close(). And  
> in my code, I had restarted_* names referring to pipefds[] making  
> it a bit confusing initially.  
>  
> How about using actual_fds[] (instead of pipefds) and expected_fds[]  
> instead of (restart_*) ?
```

I like actual\_fds[] instead of pipefds[] but still prefer the restart\_\* names over expected\_fds[].

Cheers,  
-Matt

---

Containers mailing list  
Containers@lists.linux-foundation.org  
<https://lists.linux-foundation.org/mailman/listinfo/containers>

---