
Subject: Re: [patch -mm 0/4] mqueue namespace
Posted by [ebiederm](#) on Fri, 20 Jun 2008 03:39:44 GMT
[View Forum Message](#) <> [Reply to Message](#)

ebiederm@xmission.com (Eric W. Biederman) writes:

> One way to fix that is to add a hidden directory to the mnt namespace.
> Where magic in kernel filesystems can be mounted. Only visible
> with a magic openat flag. Then:
>
> fd = openat(AT_FDKERN, ".", O_DIRECTORY)
> fchdir(fd);
> umount("./mqueue", MNT_DETACH);
> mount(("none", "./mqueue", "mqueue", 0, NULL);
>
> Would unshare the mqueue namespace.
>
> Implemented for plan9 this would solve a problem of how do you get
> access to all of it's special filesystems. As only bind mounts
> and remote filesystem mounts are available. For linux thinking about
> it might shake the conversation up a bit.

Thinking about this some more. What is especially attractive if we do
all namespaces this way is that it solves two lurking problems.

- 1) How do you keep a namespace around without a process in it.
- 2) How do you enter a container.

If we could land the namespaces in the filesystem we could easily
persist them past the point where a process is present in one if we so
choose.

Entering a container would be a matter of replacing your current
namespaces mounts with namespace mounts take from the filesystem.

I expect performance would degrade in practice, but it is tempting
to implement it and run a benchmark and see if we can measure anything.

Eric

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
