

---

Subject: [PATCH 3/3] i/o accounting and control  
Posted by [Andrea Righi](#) on Fri, 20 Jun 2008 10:05:35 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Apply the io-throttle controller to the opportune kernel functions. Both accounting and throttling functionalities are performed by `cgroup_io_throttle()`.

Signed-off-by: Andrea Righi <[righi.andrea@gmail.com](mailto:righi.andrea@gmail.com)>

---

```
block/blk-core.c | 2 ++
fs/buffer.c      | 10 ++++++++
fs/direct-io.c   | 3 +++
mm/page-writeback.c | 9 ++++++++
mm/readahead.c   | 5 +++++
5 files changed, 29 insertions(+), 0 deletions(-)
```

```
diff --git a/block/blk-core.c b/block/blk-core.c
index 1905aab..8eddef5 100644
--- a/block/blk-core.c
+++ b/block/blk-core.c
@@ -26,6 +26,7 @@
#include <linux/swap.h>
#include <linux/writeback.h>
#include <linux/task_io_accounting_ops.h>
+#include <linux/blk-io-throttle.h>
#include <linux/interrupt.h>
#include <linux/cpu.h>
#include <linux/blktrace_api.h>
@@ -1482,6 +1483,7 @@ void submit_bio(int rw, struct bio *bio)
    count_vm_events(PGPGOUT, count);
    } else {
        task_io_account_read(bio->bi_size);
+   cgroup_io_throttle(bio->bi_bdev, bio->bi_size);
        count_vm_events(PGPGIN, count);
    }
```

```
diff --git a/fs/buffer.c b/fs/buffer.c
index a073f3f..c63dfe7 100644
--- a/fs/buffer.c
+++ b/fs/buffer.c
@@ -35,6 +35,7 @@
#include <linux/suspend.h>
#include <linux/buffer_head.h>
#include <linux/task_io_accounting_ops.h>
+#include <linux/blk-io-throttle.h>
#include <linux/bio.h>
#include <linux/notifier.h>
```

```

#include <linux/cpu.h>
@@ -700,6 +701,9 @@ EXPORT_SYMBOL(mark_buffer_dirty_inode);
static int __set_page_dirty(struct page *page,
    struct address_space *mapping, int warn)
{
+ struct block_device *bdev = NULL;
+ size_t cgroup_io_acct = 0;
+
    if (unlikely(!mapping))
        return !TestSetPageDirty(page);

@@ -711,16 +715,22 @@ static int __set_page_dirty(struct page *page,
    WARN_ON_ONCE(warn && !PageUptodate(page));

    if (mapping_cap_account_dirty(mapping)) {
+ bdev = (mapping->host &&
+ mapping->host->i_sb->s_bdev) ?
+ mapping->host->i_sb->s_bdev : NULL;
+
    __inc_zone_page_state(page, NR_FILE_DIRTY);
    __inc_bdi_stat(mapping->backing_dev_info,
        BDI_RECLAIMABLE);
    task_io_account_write(PAGE_CACHE_SIZE);
+ cgroup_io_acct = PAGE_CACHE_SIZE;
    }
    radix_tree_tag_set(&mapping->page_tree,
        page_index(page), PAGECACHE_TAG_DIRTY);
    }
    write_unlock_irq(&mapping->tree_lock);
    __mark_inode_dirty(mapping->host, I_DIRTY_PAGES);
+ cgroup_io_throttle(bdev, cgroup_io_acct);

    return 1;
}
diff --git a/fs/direct-io.c b/fs/direct-io.c
index 9e81add..fe991ac 100644
--- a/fs/direct-io.c
+++ b/fs/direct-io.c
@@ -35,6 +35,7 @@
#include <linux/buffer_head.h>
#include <linux/rwsem.h>
#include <linux/uio.h>
+#include <linux/blk-io-throttle.h>
#include <asm/atomic.h>

/*
@@ -666,6 +667,8 @@ submit_page_section(struct dio *dio, struct page *page,
/*

```

```

    * Read accounting is performed in submit_bio()
    */
+ struct block_device *bdev = dio->bio ? dio->bio->bi_bdev : NULL;
+ cgroup_io_throttle(bdev, len);
  task_io_account_write(len);
}

diff --git a/mm/page-writeback.c b/mm/page-writeback.c
index 789b6ad..a2b820d 100644
--- a/mm/page-writeback.c
+++ b/mm/page-writeback.c
@@ -23,6 +23,7 @@
#include <linux/init.h>
#include <linux/backing-dev.h>
#include <linux/task_io_accounting_ops.h>
+#include <linux/blk-io-throttle.h>
#include <linux/blkdev.h>
#include <linux/mpage.h>
#include <linux/rmap.h>
@@ -1077,6 +1078,8 @@ int __set_page_dirty_nobuffers(struct page *page)
if (!TestSetPageDirty(page)) {
    struct address_space *mapping = page_mapping(page);
    struct address_space *mapping2;
+ struct block_device *bdev = NULL;
+ size_t cgroup_io_acct = 0;

    if (!mapping)
        return 1;
@@ -1087,10 +1090,15 @@ int __set_page_dirty_nobuffers(struct page *page)
    BUG_ON(mapping2 != mapping);
    WARN_ON_ONCE(!PagePrivate(page) && !PageUptodate(page));
    if (mapping_cap_account_dirty(mapping)) {
+ bdev = (mapping->host &&
+ mapping->host->i_sb->s_bdev) ?
+ mapping->host->i_sb->s_bdev : NULL;
+
        __inc_zone_page_state(page, NR_FILE_DIRTY);
        __inc_bdi_stat(mapping->backing_dev_info,
            BDI_RECLAIMABLE);
        task_io_account_write(PAGE_CACHE_SIZE);
+ cgroup_io_acct = PAGE_CACHE_SIZE;
    }
    radix_tree_tag_set(&mapping->page_tree,
        page_index(page), PAGECACHE_TAG_DIRTY);
@@ -1100,6 +1108,7 @@ int __set_page_dirty_nobuffers(struct page *page)
/* !PageAnon && !swapper_space */
    __mark_inode_dirty(mapping->host, I_DIRTY_PAGES);
}

```

```

+ cgroup_io_throttle(bdev, cgroup_io_acct);
  return 1;
}
  return 0;
diff --git a/mm/readahead.c b/mm/readahead.c
index d8723a5..dff6b02 100644
--- a/mm/readahead.c
+++ b/mm/readahead.c
@@ -14,6 +14,7 @@
#include <linux/blkdev.h>
#include <linux/backing-dev.h>
#include <linux/task_io_accounting_ops.h>
+#include <linux/blk-io-throttle.h>
#include <linux/pagevec.h>
#include <linux/pagemap.h>

@@ -58,6 +59,9 @@ int read_cache_pages(struct address_space *mapping, struct list_head
*pages,
    int (*filler)(void *, struct page *), void *data)
{
    struct page *page;
+ struct block_device *bdev =
+ (mapping->host && mapping->host->i_sb->s_bdev) ?
+ mapping->host->i_sb->s_bdev : NULL;
    int ret = 0;

    while (!list_empty(pages)) {
@@ -76,6 +80,7 @@ int read_cache_pages(struct address_space *mapping, struct list_head
*pages,
        break;
    }
    task_io_account_read(PAGE_CACHE_SIZE);
+ cgroup_io_throttle(bdev, PAGE_CACHE_SIZE);
}
    return ret;
}
--
1.5.4.3

```

---

Containers mailing list  
Containers@lists.linux-foundation.org  
<https://lists.linux-foundation.org/mailman/listinfo/containers>

---