
Subject: [PATCH 2/8] CGroup Files: Add write_string cgroup control file method
Posted by [Paul Menage](#) on Fri, 20 Jun 2008 23:44:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

This patch adds a write_string() method for cgroups control files. The semantics are that a buffer is copied from userspace to kernel space and the handler function invoked on that buffer. The buffer is guaranteed to be nul-terminated, and no longer than max_write_len (defaulting to 64 bytes if unspecified). Later patches will convert existing raw file write handlers in control group subsystems to use this method.

Signed-off-by: Paul Menage <menage@google.com>

```
include/linux/cgroup.h | 14 ++++++
kernel/cgroup.c       | 35 ++++++
2 files changed, 49 insertions(+)
```

Index: cws-2.6.26-rc5-mm3/include/linux/cgroup.h

```
=====
--- cws-2.6.26-rc5-mm3.orig/include/linux/cgroup.h
+++ cws-2.6.26-rc5-mm3/include/linux/cgroup.h
@@ -205,6 +205,13 @@ struct cftype {
     * subsystem, followed by a period */
     char name[MAX_CFTYPE_NAME];
     int private;
+
+ /*
+ * If non-zero, defines the maximum length of string that can
+ * be passed to write_string; defaults to 64
+ */
+ size_t max_write_len;
+
     int (*open)(struct inode *inode, struct file *file);
     ssize_t (*read)(struct cgroup *cgrp, struct cftype *cft,
                    struct file *file,
@@ -249,6 +256,13 @@ struct cftype {
     int (*write_s64)(struct cgroup *cgrp, struct cftype *cft, s64 val);

     /*
+ * write_string() is passed a nul-terminated kernel space
+ * buffer of maximum length determined by max_write_len.
+ * Returns 0 or -ve error code.
+ */
+ int (*write_string)(struct cgroup *cgrp, struct cftype *cft,
+                    const char *buffer);
+ /*
```

* trigger() callback can be used to get some kick from the
* userspace, when the actual string written is not important
* at all. The private field can be used to determine the

Index: cws-2.6.26-rc5-mm3/kernel/cgroup.c

```
=====
--- cws-2.6.26-rc5-mm3.orig/kernel/cgroup.c
+++ cws-2.6.26-rc5-mm3/kernel/cgroup.c
@@ -1363,6 +1363,39 @@ static ssize_t cgroup_write_X64(struct c
    return retval;
}

+static ssize_t cgroup_write_string(struct cgroup *cgrp, struct cftype *cft,
+    struct file *file,
+    const char __user *userbuf,
+    size_t nbytes, loff_t *unused_ppos)
+{
+    char local_buffer[64];
+    int retval = 0;
+    size_t max_bytes = cft->max_write_len;
+    char *buffer = local_buffer;
+
+    if (!max_bytes)
+        max_bytes = sizeof(local_buffer) - 1;
+    if (nbytes >= max_bytes)
+        return -E2BIG;
+    /* Allocate a dynamic buffer if we need one */
+    if (nbytes >= sizeof(local_buffer)) {
+        buffer = kmalloc(nbytes + 1, GFP_KERNEL);
+        if (buffer == NULL)
+            return -ENOMEM;
+    }
+    if (nbytes && copy_from_user(buffer, userbuf, nbytes))
+        return -EFAULT;
+
+    buffer[nbytes] = 0;    /* nul-terminate */
+    strstrip(buffer);
+    retval = cft->write_string(cgrp, cft, buffer);
+    if (!retval)
+        retval = nbytes;
+    if (buffer != local_buffer)
+        kfree(buffer);
+    return retval;
+}
+
static ssize_t cgroup_common_file_write(struct cgroup *cgrp,
    struct cftype *cft,
    struct file *file,
@@ -1440,6 +1473,8 @@ static ssize_t cgroup_file_write(struct
```

```
    return cft->write(cgrp, cft, file, buf, nbytes, ppos);
    if (cft->write_u64 || cft->write_s64)
        return cgroup_write_X64(cgrp, cft, file, buf, nbytes, ppos);
+ if (cft->write_string)
+ return cgroup_write_string(cgrp, cft, file, buf, nbytes, ppos);
    if (cft->trigger) {
        int ret = cft->trigger(cgrp, (unsigned int)cft->private);
        return ret ? ret : nbytes;
    }
--
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
