
Subject: Re: [PATCH 06/11] sysfs: Implement sysfs tagged directory support.
Posted by [Tejun Heo](#) on Thu, 03 Jul 2008 15:58:23 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hello,

Eric W. Biederman wrote:

> Daniel Lezcano <dlezcano@fr.ibm.com> writes:

>
>> The kobject events are sent through a netlink message which is not currently per
>> network namespace. Shouldn't be useful to have a way to retrieve from the
>> kobject the network namespace or the uevent socket associated with it ? IMHO
>> having idr in the kobject + netns pointer associated may help to handle the
>> sysfs isolation and makes the uevent per namespace trivial, no ?

>

> Grumble. I have been conveniently been forgetting about that socket.

> Similarly we have the user mode helpers to deal with.

>

> For this conversation there is a simple answer. All of that is in the
> kobject layer, and works even when you compile sysfs out of your kernel.
> Therefore it is a separate problem. And sysfs idr tags have nothing
> to do with it.

>

> It is most definitely something we need to come back to. I bet there
> are some interesting interactions when you have multiple network devices
> with the same name generating events.

Related delta: I've been thinking that uevents should be part of sysfs
not kobject as that's what the userland is gonna associate the event
with. Would that solve the problem you're thinking about?

Thanks.

--

tejun

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
