Subject: [PATCH net-next 4/9] netns: register net.ipv4.route.flush in each namespace
Posted by den on Fri, 04 Jul 2008 13:17:07 GMT
View Forum Message <> Reply to Message

Signed-off-by: Denis V. Lunev <den@openvz.org>
---
 include/net/netns/ipv4.h | 1 +
 net/ipv4/route.c | 79 ++++++

```
  int delay;
+ struct net *net;
  if (newlen != sizeof(int))
   return -EINVAL;
  if (get_user(delay, (int __user *)newval))
   return -EFAULT;
- rt_cache_flush(&init_net, delay);
+ net = (struct net *)table->extra1;
+ rt_cache_flush(net, delay);
  return 0;
 }

 ctl_table ipv4_route_table[] = {
  {
-  .ctl_name  = NET_IPV4_ROUTE_FLUSH,
-  .procname = "flush",
-  .maxlen  = sizeof(int),
-  .mode  = 0200,
-  .proc_handler = &ipv4_sysctl_rtcache_flush,
-  .strategy = &ipv4_sysctl_rtcache_flush_strategy,
- },
- {
   .ctl_name = NET_IPV4_ROUTE_GC_THRESH,
   .procname = "gc_thresh",
   .data  = &ipv4_dst_ops.gc_thresh,
@@ -3014,6 +3010,66 @@ ctl_table ipv4_route_table[] = {
  },
  { .ctl_name = 0 }
 };
+
+static __net_initdata struct ctl_path ipv4_route_path[] = {
+ { .procname = "net", .ctl_name = CTL_NET, },
+ { .procname = "ipv4", .ctl_name = NET_IPV4, },
+ { .procname = "route", .ctl_name = NET_IPV4_ROUTE, },
+ { },
+};
+
+
+static struct ctl_table ipv4_route_flush_table[] = {
+ {
+  .ctl_name  = NET_IPV4_ROUTE_FLUSH,
+  .procname = "flush",
+  .maxlen  = sizeof(int),
+  .mode  = 0200,
+  .proc_handler = &ipv4_sysctl_rtcache_flush,
+  .strategy = &ipv4_sysctl_rtcache_flush_strategy,
+ },
+ { .ctl_name = 0 },
```

```
+};
+
+static __net_init int sysctl_route_net_init(struct net *net)
+{
+ struct ctl_table *tbl;
+
+ tbl = ipv4_route_flush_table;
+ if (net != &init_net) {
+  tbl = kmemdup(tbl, sizeof(ipv4_route_flush_table), GFP_KERNEL);
+  if (tbl == NULL)
+   goto err_dup;
+ }
+ tbl[0].extra1 = net;
+
+ net->ipv4.route_hdr =
+  register_net_sysctl_table(net, ipv4_route_path, tbl);
+ if (net->ipv4.route_hdr == NULL)
+  goto err_reg;
+ return 0;
+
+err_reg:
+ if (tbl != ipv4_route_flush_table)
+  kfree(tbl);
+err_dup:
+ return -ENOMEM;
+}
+
+static __net_exit void sysctl_route_net_exit(struct net *net)
+{
+ struct ctl_table *tbl;
+
+ tbl = net->ipv4.route_hdr->ctl_table_arg;
+ unregister_net_sysctl_table(net->ipv4.route_hdr);
+ BUG_ON(tbl == ipv4_route_flush_table);
+ kfree(tbl);
+}
+
+static __net_initdata struct pernet_operations sysctl_route_ops = {
+ .init = sysctl_route_net_init,
+ .exit = sysctl_route_net_exit,
+};
 #endif

 #ifdef CONFIG_NET_CLS_ROUTE
@@ -3090,6 +3146,9 @@ int __init ip_rt_init(void)
 #endif
  rtnl_register(PF_INET, RTM_GETROUTE, inet_rtm_getroute, NULL);
```

```
+#ifdef CONFIG_SYSCTL
+ register_pernet_subsys(&sysctl_route_ops);
+#endif
  return rc;
 }

--
1.5.3.rc5
```

_____
Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers