
Subject: Re: Re: [RFC PATCH 0/5] Resend - Use procfs to change a syscall behavior

Posted by [Nadia Derby](#) on Thu, 10 Jul 2008 10:11:20 GMT

[View Forum Message](#) <> [Reply to Message](#)

Paul Menage wrote:

> On Thu, Jul 10, 2008 at 2:14 AM, Nadia Derby <Nadia.Derbey@bull.net> wrote:

>

>>But I think that both ways of doing are not exactly the same in case of

>>failure:

>>open + dup2 will close newfd if it is already busy.

>>while

>>next-syscall_data + open will fail if the target fd is already busy. And

>>that's the functionality we need during restart, isn't it?

>

>

> No, I don't think so. The cryo restart code should be aware of exactly
> which fds it has open and which it needs to open, and can shuffle them
> around as necessary via dup2() to get them into the right places.

>

Yes sure, that's exactly what it does.

what I just wanted to say here is that the concept of opening + dup2'ing
is not exactly the same as the open_with_id concept.

But I agree with you: a restart code knows exactly what it does and can
safely play with the open and dup syscalls.

Regards,
Nadia

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
