

---

Subject: Re: [PATCH 12/15] driver core: Implement tagged directory support for device classes.

Posted by [ebiederm](#) on Wed, 16 Jul 2008 05:41:14 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Tejun Heo <[htejun@gmail.com](mailto:htejun@gmail.com)> writes:

> Greg, please disregard my earlier NACKs and commit the patches if you're  
> okay with them. I'm working on cleaning it up but I don't think I'll be  
> able to make it in time for merge window and as Eric said getting the  
> functionality in place is more important at this point as it doesn't  
> affect user visible interface.

>

> Eric, with the multiple superblocks, sysfs now uses inode from the  
> default sysfs\_sb with dentries from other sb's. Is this okay? Are  
> there any other filesystems which do this?

I don't know of any other filesystems where this unique challenge arises.  
/proc almost qualifies but it never needs to be modified.

It is certainly ok to go from multiple dentries to a single inode.  
I'm trying to remember why I choose to do that. I think both because it simplifies  
the locking and keeps us more efficient in the icache.

Eric

---

Containers mailing list  
[Containers@lists.linux-foundation.org](mailto:Containers@lists.linux-foundation.org)  
<https://lists.linux-foundation.org/mailman/listinfo/containers>

---