
Subject: Networking/IPTables, cannot ping domains names from container with iptables on in HZ

Posted by [openxs](#) on Thu, 31 Jul 2008 19:11:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

IPTables problem 31/07/08

I am running a server from home using dynDNS. I can ping internal/external IP addresses from my VPS (which is called 101) without a problem, but if I try to ping a domain name it will not resolve and I get: unknown host google.co.uk.

Sorry if this question has already been answered, I have found posts with similar problems but the set up is generally different. I'm pretty sure I have not configured the iptables correctly.

I come to this conclusion because if I switch off IPTables on the HN then restart VPS 101, domains start to resolve on VPS 101, but I'm not sure that this is a good way to run the server...

This is what I have set up:

```
# uname -rm = 2.6.18-53.1.19.el5.028stab053.14ent i686
vzctl version 3.0.22
HN = CentOS 5 with IP: 192.168.1.2
VPS 101 = CentOS 5 with IP: 192.168.1.5
Router = 192.168.1.1 (I have reserved 192.168.1.2 - 19 for static addresses)
```

I set this up following the quick start guide on the wiki, but I was a little uncertain about /etc/sysctl.conf, I have added the contents of my file below.

I also tried this from the OpenVZ wiki. Ref:
http://wiki.openvz.org/Using_NAT_for_container_with_private_IPs

**** How to provide access for container to Internet ****

To enable the containers, which have only internal IP addresses, to access the Internet, SNAT (Source Network Address Translation, also known as IP masquerading) should be configured on the Hardware Node. This is ensured by the standard Linux iptables utility. To perform a simple SNAT setup, execute the following command on the Hardware Node:

```
# iptables -t nat -A POSTROUTING -s src_net -o eth0 -j SNAT --to ip_address
```

Mine looks like this:

```
# iptables -t nat -A POSTROUTING -s 192.168.1.5/19 -o eth0 -j SNAT --to 192.168.1.2
```

I have turned iptables off so I can carry on using just my hardware firewall, do I actually need IPTables on the HZ? I would feel happier using/learning it. Am I missing something, I have to admit I have never really had to play with IPTables before so this is uncharted territory for me.

I found this post in the forums, but these guys solved the problem by switching IPTables off...
Ref: <http://forum.openvz.org/index.php?t=msg&goto=11896&>

Here are the contents of the files I modified during the install.

```
# cat /etc/modprobe.conf
```

```
options ip_conntrack ip_conntrack_enable_ve0=1
alias eth0 tg3
alias scsi_hostadapter ata_piix
```

```
# cat /etc/sysctl.conf
```

```
# Kernel sysctl configuration file for Red Hat Linux
```

```
#
```

```
# For binary values, 0 is disabled, 1 is enabled. See sysctl( and
# sysctl.conf(5) for more details.
```

```
# Controls IP packet forwarding
```

```
net.ipv4.ip_forward = 1
net.ipv4.conf.default.proxy_arp = 0
```

```
# Controls source route verification
```

```
net.ipv4.conf.default.rp_filter = 1
net.ipv4.conf.all.rp_filter = 1
```

```
# Do not accept source routing
```

```
net.ipv4.conf.default.accept_source_route = 0
```

```
# Controls the System Request debugging functionality of the kernel
```

```
kernel.sysrq = 1
```

```
# Controls whether core dumps will append the PID to the core filename
```

```
# Useful for debugging multi-threaded applications
```

```
kernel.core_uses_pid = 1
```

```
# Controls the use of TCP syncookies
```

```
net.ipv4.tcp_syncookies = 1
```

```
# Controls the maximum size of a message, in bytes
```

```
kernel.msgmnb = 65536
```

```
# Controls the default maximum size of a message queue
```

```
kernel.msgmax = 65536
```

```
# Controls the maximum shared segment size, in bytes
```

```
kernel.shmmax = 4294967295
```

```
# Controls the maximum number of shared memory segments, in pages
kernel.shmall = 268435456
```

```
# We do not want all our interfaces to send redirects
net.ipv4.conf.default.send_redirects = 1
net.ipv4.conf.all.send_redirects = 0
```

Here is some other information that might be useful:

Commands run on the HZ:

```
# ifconfig
```

```
eth0  Link encap:Ethernet HWaddr 00:21:5A:51:39:75
      inet addr:192.168.1.2 Bcast:192.168.1.255 Mask:255.255.255.0
      inet6 addr: fe80::221:5aff:fe51:3975/64 Scope:Link
      UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
      RX packets:443 errors:0 dropped:0 overruns:0 frame:0
      TX packets:333 errors:0 dropped:0 overruns:0 carrier:0
      collisions:0 txqueuelen:1000
      RX bytes:39090 (38.1 KiB) TX bytes:51661 (50.4 KiB)
      Interrupt:177
```

```
lo    Link encap:Local Loopback
      inet addr:127.0.0.1 Mask:255.0.0.0
      inet6 addr: ::1/128 Scope:Host
      UP LOOPBACK RUNNING MTU:16436 Metric:1
      RX packets:8 errors:0 dropped:0 overruns:0 frame:0
      TX packets:8 errors:0 dropped:0 overruns:0 carrier:0
      collisions:0 txqueuelen:0
      RX bytes:560 (560.0 b) TX bytes:560 (560.0 b)
```

```
venet0 Link encap:UNSPEC HWaddr 00-00-00-00-00-00-00-00-00-00-00-00-00-00-00-00
      UP BROADCAST POINTOPOINT RUNNING NOARP MTU:1500 Metric:1
      RX packets:4 errors:0 dropped:0 overruns:0 frame:0
      TX packets:4 errors:0 dropped:0 overruns:0 carrier:0
      collisions:0 txqueuelen:0
      RX bytes:268 (268.0 b) TX bytes:380 (380.0 b)
```

```
# ip route list table all
```

```
192.168.1.5 dev venet0 scope link
192.168.1.0/24 dev eth0 proto kernel scope link src 192.168.1.2
169.254.0.0/16 dev eth0 scope link
default via 192.168.1.1 dev eth0
broadcast 192.168.1.0 dev eth0 table 255 proto kernel scope link src 192.168.1.2
```

```

broadcast 127.255.255.255 dev lo table 255 proto kernel scope link src 127.0.0.1
local 192.168.1.2 dev eth0 table 255 proto kernel scope host src 192.168.1.2
broadcast 192.168.1.255 dev eth0 table 255 proto kernel scope link src 192.168.1.2
broadcast 127.0.0.0 dev lo table 255 proto kernel scope link src 127.0.0.1
local 127.0.0.1 dev lo table 255 proto kernel scope host src 127.0.0.1
local 127.0.0.0/8 dev lo table 255 proto kernel scope host src 127.0.0.1
fe80::/64 dev eth0 metric 256 expires 21334181sec mtu 1500 advmss 1440 hoplimit
4294967295
unreachable default dev lo table unspec proto none metric -1 error -101 hoplimit 255
local ::1 via :: dev lo table 255 proto none metric 0 mtu 16436 advmss 16376 hoplimit
4294967295
local fe80::221:5aff:fe51:3975 via :: dev lo table 255 proto none metric 0 mtu 16436 advmss
16376 hoplimit 4294967295
ff00::/8 dev eth0 table 255 metric 256 expires 21334181sec mtu 1500 advmss 1440 hoplimit
4294967295
unreachable default dev lo table unspec proto none metric -1 error -101 hoplimit 255

```

```
# iptables -t nat -L && iptables -t filter -L && iptables -t mangle -L
```

```
Chain PREROUTING (policy ACCEPT)
```

```
target prot opt source destination
```

```
Chain POSTROUTING (policy ACCEPT)
```

```
target prot opt source destination
```

```
Chain OUTPUT (policy ACCEPT)
```

```
target prot opt source destination
```

```
Chain INPUT (policy ACCEPT)
```

```
target prot opt source destination
```

```
RH-Firewall-1-INPUT all -- anywhere anywhere
```

```
Chain FORWARD (policy ACCEPT)
```

```
target prot opt source destination
```

```
RH-Firewall-1-INPUT all -- anywhere anywhere
```

```
Chain OUTPUT (policy ACCEPT)
```

```
target prot opt source destination
```

```
Chain RH-Firewall-1-INPUT (2 references)
```

```
target prot opt source destination
```

```
ACCEPT all -- anywhere anywhere
```

```
ACCEPT icmp -- anywhere anywhere icmp any
```

```
ACCEPT esp -- anywhere anywhere
```

```
ACCEPT ah -- anywhere anywhere
```

```
ACCEPT udp -- anywhere 224.0.0.251 udp dpt:mdns
```

```
ACCEPT udp -- anywhere anywhere udp dpt:ipp
```

```
ACCEPT tcp -- anywhere anywhere tcp dpt:ipp
ACCEPT all -- anywhere anywhere state RELATED,ESTABLISHED
ACCEPT tcp -- anywhere anywhere state NEW tcp dpt:ssh
ACCEPT tcp -- anywhere anywhere state NEW tcp dpt:http
ACCEPT tcp -- anywhere anywhere state NEW tcp dpt:https
REJECT all -- anywhere anywhere reject-with icmp-host-prohibited
```

```
Chain PREROUTING (policy ACCEPT)
target prot opt source destination
```

```
Chain INPUT (policy ACCEPT)
target prot opt source destination
```

```
Chain FORWARD (policy ACCEPT)
target prot opt source destination
```

```
Chain OUTPUT (policy ACCEPT)
target prot opt source destination
```

```
Chain POSTROUTING (policy ACCEPT)
target prot opt source destination
```

```
# arp -n
Address HWtype HWaddress Flags Mask Iface
192.168.1.21 ether 00:19:7E:21:74:82 C eth0
192.168.1.1 ether 00:18:F8:4B:6D:96 C eth0
192.168.1.5 * * MP eth0
```

```
# ip a l
2: lo: <LOOPBACK,UP,LOWER_UP> mtu 16436 qdisc noqueue
link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
inet 127.0.0.1/8 scope host lo
inet6 ::1/128 scope host
valid_lft forever preferred_lft forever
4: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
link/ether 00:21:5a:51:39:75 brd ff:ff:ff:ff:ff:ff
inet 192.168.1.2/24 brd 192.168.1.255 scope global eth0
inet6 fe80::221:5aff:fe51:3975/64 scope link
valid_lft forever preferred_lft forever
6: sit0: <NOARP> mtu 1480 qdisc noop
link/sit 0.0.0.0 brd 0.0.0.0
1: venet0: <BROADCAST,POINTOPOINT,NOARP,UP,LOWER_UP> mtu 1500 qdisc noqueue
link/void
```

```
# ip r l
192.168.1.5 dev venet0 scope link
192.168.1.0/24 dev eth0 proto kernel scope link src 192.168.1.2
169.254.0.0/16 dev eth0 scope link
```

default via 192.168.1.1 dev eth0

Now the same commands on the VPS 101...

```
# ifconfig
```

```
lo    Link encap:Local Loopback
      inet addr:127.0.0.1  Mask:255.0.0.0
      inet6 addr: ::1/128 Scope:Host
      UP LOOPBACK RUNNING MTU:16436 Metric:1
      RX packets:0 errors:0 dropped:0 overruns:0 frame:0
      TX packets:0 errors:0 dropped:0 overruns:0 carrier:0
      collisions:0 txqueuelen:0
      RX bytes:0 (0.0 b) TX bytes:0 (0.0 b)
```

```
venet0 Link encap:UNSPEC HWaddr 00-00-00-00-00-00-00-00-00-00-00-00-00-00-00-00
      inet addr:127.0.0.1 P-t-P:127.0.0.1 Bcast:0.0.0.0 Mask:255.255.255.255
      UP BROADCAST POINTOPOINT RUNNING NOARP MTU:1500 Metric:1
      RX packets:4 errors:0 dropped:0 overruns:0 frame:0
      TX packets:4 errors:0 dropped:0 overruns:0 carrier:0
      collisions:0 txqueuelen:0
      RX bytes:380 (380.0 b) TX bytes:268 (268.0 b)
```

```
venet0:0 Link encap:UNSPEC HWaddr 00-00-00-00-00-00-00-00-00-00-00-00-00-00-00-00
      inet addr:192.168.1.5 P-t-P:192.168.1.5 Bcast:192.168.1.5 Mask:255.255.255.255
      UP BROADCAST POINTOPOINT RUNNING NOARP MTU:1500 Metric:1
```

```
# ip route list table all
```

```
192.0.2.0/24 dev venet0 scope host
169.254.0.0/16 dev venet0 scope link
default via 192.0.2.1 dev venet0
broadcast 127.255.255.255 dev lo table 255 proto kernel scope link src 127.0.0.1
local 192.168.1.5 dev venet0 table 255 proto kernel scope host src 192.168.1.5
broadcast 192.168.1.5 dev venet0 table 255 proto kernel scope link src 192.168.1.5
broadcast 127.0.0.0 dev lo table 255 proto kernel scope link src 127.0.0.1
local 127.0.0.1 dev lo table 255 proto kernel scope host src 127.0.0.1
local 127.0.0.1 dev venet0 table 255 proto kernel scope host src 127.0.0.1
local 127.0.0.0/8 dev lo table 255 proto kernel scope host src 127.0.0.1
unreachable default dev lo table unspec proto none metric -1 error -101 hoplimit 255
local ::1 via :: dev lo table 255 proto none metric 0 mtu 16436 advmss 16376 hoplimit
4294967295
unreachable default dev lo table unspec proto none metric -1 error -101 hoplimit 255
```

```
# iptables -t nat -L && iptables -t filter -L && iptables -t mangle -L
```

```
iptables v1.3.5: can't initialize iptables table `nat': Table does not exist (do you need to insmod?)
```

Perhaps iptables or your kernel needs to be upgraded.

```
# ip a l
```

```
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 16436 qdisc noqueue  
   link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00  
   inet 127.0.0.1/8 scope host lo  
   inet6 ::1/128 scope host  
       valid_lft forever preferred_lft forever  
3: venet0: <BROADCAST,POINTOPOINT,NOARP,UP,LOWER_UP> mtu 1500 qdisc noqueue  
   link/void  
   inet 127.0.0.1/32 scope host venet0  
   inet 192.168.1.5/32 brd 192.168.1.5 scope global venet0:0
```

```
# ip r l
```

```
192.0.2.0/24 dev venet0 scope host  
169.254.0.0/16 dev venet0 scope link  
default via 192.0.2.1 dev venet0
```

If there is more information I can provide that may help then let me know, thanks.
