

---

Subject: [PATCH 7/9] namespaces: utsname: sysctl hack

Posted by [serue](#) on Thu, 18 May 2006 15:50:30 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Sysctl uts patch. This clearly will need to be done another way, but since sysctl itself needs to be container aware, 'the right thing' is a separate patchset.

Signed-off-by: Serge E. Hallyn <[serue@us.ibm.com](mailto:serue@us.ibm.com)>

---

kernel/sysctl.c | 20 +++++++-----  
1 files changed, 10 insertions(+), 10 deletions(-)

```
e03808f9c1b803ff67e396e806c062c97b4073aa
diff --git a/kernel/sysctl.c b/kernel/sysctl.c
index e82726f..ab36b41 100644
--- a/kernel/sysctl.c
+++ b/kernel/sysctl.c
@@ -233,8 +233,8 @@ static ctl_table kern_table[] = {
{
    .ctl_name = KERN_OSTYPE,
    .procname = "ostype",
-   .data = system_utsname.sysname,
-   . maxlen = sizeof(system_utsname.sysname),
+   .data = init_uts_ns.name.sysname,
+   . maxlen = sizeof(init_uts_ns.name.sysname),
    .mode = 0444,
    .proc_handler = &proc_doutsstring,
    .strategy = &sysctl_string,
@@ -242,8 +242,8 @@ static ctl_table kern_table[] = {
{
    .ctl_name = KERN_OSRELEASE,
    .procname = "osrelease",
-   .data = system_utsname.release,
-   . maxlen = sizeof(system_utsname.release),
+   .data = init_uts_ns.name.release,
+   . maxlen = sizeof(init_uts_ns.name.release),
    .mode = 0444,
    .proc_handler = &proc_doutsstring,
    .strategy = &sysctl_string,
@@ -251,8 +251,8 @@ static ctl_table kern_table[] = {
{
    .ctl_name = KERN_VERSION,
    .procname = "version",
-   .data = system_utsname.version,
-   . maxlen = sizeof(system_utsname.version),
```

```
+ .data = init_uts_ns.name.version,
+ . maxlen = sizeof(init_uts_ns.name.version),
.mode = 0444,
.proc_handler = &proc_doutsstring,
.strategy = &sysctl_string,
@@ -260,8 +260,8 @@ static ctl_table kern_table[] = {
{
.ctl_name = KERN_NODENAME,
.procname = "hostname",
- .data = system_utsname.nodename,
- . maxlen = sizeof(system_utsname.nodename),
+ .data = init_uts_ns.name.nodename,
+ . maxlen = sizeof(init_uts_ns.name.nodename),
.mode = 0644,
.proc_handler = &proc_doutsstring,
.strategy = &sysctl_string,
@@ -269,8 +269,8 @@ static ctl_table kern_table[] = {
{
.ctl_name = KERN_DOMAINNAME,
.procname = "domainname",
- .data = system_utsname.domainname,
- . maxlen = sizeof(system_utsname.domainname),
+ .data = init_uts_ns.name.domainname,
+ . maxlen = sizeof(init_uts_ns.name.domainname),
.mode = 0644,
.proc_handler = &proc_doutsstring,
.strategy = &sysctl_string,
```

--

1.1.6

---