
Subject: SOLVED: Destination Host Unreachable from VE on Public IP

Posted by [4drob](#) on Fri, 19 Sep 2008 22:47:51 GMT

[View Forum Message](#) <> [Reply to Message](#)

I'm new to OpenVZ, but have read a bit about it. My HN is running a fresh copy of Ubuntu 8.04. I followed the Debian install guide (where applicable) to configure a VE with the Ubuntu 8.04 template found on the wiki.

The VE is on it's own public IP (same subnet as the HN). The VE can ping IP addresses out on the internet and can correctly resolve domain names, but it can't ping domain names (get Destination Host Unreachable) and thus can't use apt-get to update, wget, etc.

The VE can be pinged by the HN and from inside the network by IP but not from outside the network (packets get to HN then time out). No firewall setup. Maybe I'm missing something, but I've read through all the documentation I could find, tried different variations of settings, destroyed and re-created the VE multiple times, and I'm just out of ideas. The same network does have 3 other HNs running Virtuozzo with VEs on their own public IPs working just fine. Thanks in advance for any help or suggestions!

HN:

uname -r

2.6.24-19-openvz

ip a l

1: lo: <LOOPBACK,UP,LOWER_UP> mtu 16436 qdisc noqueue

link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00

inet 127.0.0.1/8 scope host lo

inet6 ::1/128 scope host

valid_lft forever preferred_lft forever

2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 100

link/ether 00:30:48:2f:85:16 brd ff:ff:ff:ff:ff:ff

inet 67.30.129.74/23 brd 67.30.129.255 scope global eth0

inet6 fe80::230:48ff:fe2f:8516/64 scope link

valid_lft forever preferred_lft forever

3: eth1: <NO-CARRIER,BROADCAST,MULTICAST,UP> mtu 1500 qdisc pfifo_fast qlen 1000

link/ether 00:30:48:2f:85:17 brd ff:ff:ff:ff:ff:ff

inet 67.30.129.75/23 brd 67.30.129.255 scope global eth1

21: venet0: <BROADCAST,POINTOPOINT,NOARP,UP,LOWER_UP> mtu 1500 qdisc noqueue

link/void

sysctl -p

kernel.printk = 4 4 1 7 (set by Ubuntu openvz-meta installer script)

kernel.maps_protect = 1 (" ")

fs.inotify.max_user_watches = 524288 (" ")

error: "vm.mmap_min_addr" is an unknown key (set to 65536 by script)

net.ipv4.conf.default.forwarding = 1

net.ipv4.conf.default.proxy_arp = 0

net.ipv4.ip_forward = 1

```
net.ipv4.conf.all.rp_filter = 1
net.ipv4.conf.default.send_redirects = 1
net.ipv4.conf.all.send_redirects = 0
kernel.sysrq = 1
```

ip rule list

```
0:    from all lookup local
32766: from all lookup main
32767: from all lookup default
```

```
iptables -t nat -L && iptables -t filter -L && iptables -t mangle -L
```

Chain PREROUTING (policy ACCEPT)

```
target    prot opt source                destination
```

Chain POSTROUTING (policy ACCEPT)

```
target    prot opt source                destination
```

Chain OUTPUT (policy ACCEPT)

```
target    prot opt source                destination
```

Chain INPUT (policy ACCEPT)

```
target    prot opt source                destination
```

Chain FORWARD (policy ACCEPT)

```
target    prot opt source                destination
```

Chain OUTPUT (policy ACCEPT)

```
target    prot opt source                destination
```

Chain PREROUTING (policy ACCEPT)

```
target    prot opt source                destination
```

Chain INPUT (policy ACCEPT)

```
target    prot opt source                destination
```

Chain FORWARD (policy ACCEPT)

```
target    prot opt source                destination
```

Chain OUTPUT (policy ACCEPT)

```
target    prot opt source                destination
```

Chain POSTROUTING (policy ACCEPT)

```
target    prot opt source                destination
```

VE:

```
ping google.com
```

```
PING google.com (64.233.167.99) 56(84) bytes of data.
```

```
From 67-30-129-74.4servers.com (67.30.129.74) icmp_seq=7 Destination Host Unreachable
```

```
ping 67.30.129.74
```

```
PING 67.30.129.74 (67.30.129.74) 56(84) bytes of data.
```

```
64 bytes from 67.30.129.74: icmp_seq=1 ttl=64 time=0.074 ms
```

```
tcpdump -i venet0:0 -e -n host google.com
```

```
-bash: tcpdump: command not found
```

ip a l

```
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 16436 qdisc noqueue
```

```
link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
inet 127.0.0.1/8 scope host lo
inet6 ::1/128 scope host
    valid_lft forever preferred_lft forever
2: venet0: <BROADCAST,POINTOPOINT,NOARP,UP,LOWER_UP> mtu 1500 qdisc noqueue
    link/void
    inet 127.0.0.1/32 scope host venet0
    inet 67.30.129.76/32 scope global venet0:0
```

```
ip route list table all
192.0.2.1 dev venet0 scope link
default via 192.0.2.1 dev venet0
broadcast 127.255.255.255 dev lo table local proto kernel scope link src 127.0.0.1
local 67.30.129.76 dev venet0 table local proto kernel scope host src 67.30.129.76
broadcast 127.0.0.0 dev lo table local proto kernel scope link src 127.0.0.1
local 127.0.0.1 dev lo table local proto kernel scope host src 127.0.0.1
local 127.0.0.1 dev venet0 table local proto kernel scope host src 127.0.0.1
local 127.0.0.0/8 dev lo table local proto kernel scope host src 127.0.0.1
unreachable default dev lo table unspec proto none metric -1 error -101 hoplimit 255
local ::1 via :: dev lo table local proto none metric 0 mtu 16436 advmss 16376 hoplimit
4294967295
unreachable default dev lo table unspec proto none metric -1 error -101 hoplimit 255
```

```
ip -V
ip utility, iproute2-ss071016
```

```
from my box outside the network
tracert 67.30.129.76
```

```
[snip]
 9  75 ms  74 ms  76 ms so-3-0-0.mp1.Tustin1.Level3.net [209.247.8.118]
10  77 ms  75 ms  76 ms so-9-0.hsa1.Tustin1.Level3.net [4.68.114.6]
11  77 ms  77 ms  78 ms 65.58.240.18
12  78 ms  79 ms  79 ms 67-30-129-74.4servers.com [67.30.129.74]
13  *      *      *      Request timed out.
```
