
Subject: Re: [PATCH 3/3] proc: make UTS-related sysctls utsns aware
Posted by [Dave Hansen](#) on Wed, 24 May 2006 18:02:57 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Tue, 2006-05-23 at 13:23 +1200, Sam Vilain wrote:

```
>
> + /* map the filename to the pointer. perhaps it would be
> better
> +
> +     to put struct offset pointers in table->data ? */
> + switch (filp->f_dentry->d_name.name[3]) {
> +     case 'y': /* ostYpe */
> +         which = uts_ns->name.sysname;
> +         break;
> +     case 't': /* hosTname */
> +         which = uts_ns->name.nodename;
> +         break;
> +     case 'e': /* osrElease */
> +         which = uts_ns->name.release;
> +         break;
> +     case 's': /* verSion */
> +         which = uts_ns->name.version;
> +         break;
> +     case 'x': /* XXX - unreachable */
> +         which = uts_ns->name.machine;
> +         break;
> +     case 'a': /* domAinname */
> +         which = uts_ns->name.domainname;
> +         break;
> +     default:
> +         printk("procfs: impossible uts part '%s",
> +               (char*)filp->f_dentry->d_name.name);
> +         r = -EINVAL;
> +         goto out;
> + }
```

Why not just switch on the ->ctl_name from the table? Wouldn't that be easier?

-- Dave
