
Subject: Re: install error

Posted by [ft.linux](#) on Tue, 18 Nov 2008 01:27:47 GMT

[View Forum Message](#) <> [Reply to Message](#)

cat /etc/sysctl.conf

```
# Kernel sysctl configuration file for Red Hat Linux
#
# For binary values, 0 is disabled, 1 is enabled. See sysctl( and
# sysctl.conf(5) for more details.

# Controls IP packet forwarding
net.ipv4.ip_forward = 1 ### openvz
net.ipv4.conf.default.proxy_arp = 0 ### openvz
net.ipv4.conf.all.rp_filter = 1 ### openvz
net.ipv4.conf.default.send_redirects = 1 ### openvz
net.ipv4.conf.all.send_redirects = 0 ### openvz
net.ipv4.icmp_echo_ignore_broadcasts = 1 ### openvz
net.ipv4.conf.default.forwarding = 1 ### openvz

# Controls source route verification
net.ipv4.conf.default.rp_filter = 1

# Do not accept source routing
net.ipv4.conf.default.accept_source_route = 0

# Controls the System Request debugging functionality of the kernel
kernel.sysrq = 1 ### openvz

# Controls whether core dumps will append the PID to the core filename
# Useful for debugging multi-threaded applications
kernel.core_uses_pid = 1

# Controls the use of TCP syncookies
net.ipv4.tcp_syncookies = 1

# Controls the maximum size of a message, in bytes
kernel.msgmnb = 65536

# Controls the default maximum size of a message queue
kernel.msgmax = 65536

# Controls the maximum shared segment size, in bytes
kernel.shmmmax = 4294967295

# Controls the maximum number of shared memory segments, in pages
kernel.shmall = 268435456
```
