
Subject: Re: How about post-VE-start scripts?

Posted by [piavlo](#) on Thu, 11 Dec 2008 08:57:55 GMT

[View Forum Message](#) <> [Reply to Message](#)

You can use `/etc/vz/conf/vps.mount` & `/etc/vz/conf/vps.umount` scripts, here is how i've done it:

```
projsrv3 ~ # cat /etc/vz/conf/vps.mount
#!/bin/bash
```

```
if [ -x /vz/root/${VEID}/.cs-chroot.start ]; then
    /vz/root/${VEID}/.cs-chroot.start
    exit $?
fi
```

```
projsrv3 ~ # cat /etc/vz/conf/vps.umount
#!/bin/bash
```

```
if [ -x /vz/root/${VEID}/.cs-chroot.stop ]; then
    /vz/root/${VEID}/.cs-chroot.stop
    exit $?
fi
```

```
projsrv3 ~ # cat /vz/root/103/.cs-chroot.start
#!/bin/bash
```

```
mount -n --bind /vz/template/portage $(dirname $0)/usr/portage || exit ${?}
mount -n --bind /vz/template/portage-distfiles $(dirname $0)/usr/portage/distfiles || exit ${?}
mount -n --bind /vz/template/portage-packages $(dirname $0)/usr/portage/packages || exit ${?}
projsrv3 ~ # cat /vz/root/103/.cs-chroot.stop
#!/bin/bash
```

```
umount $(dirname $0)/usr/portage/packages
umount $(dirname $0)/usr/portage/distfiles
umount $(dirname $0)/usr/portage
projsrv3 ~ #
```
