
Posted by [anray](#) on Thu, 29 Jan 2009 20:19:48 GMT

[View Forum Message](#) <> [Reply to Message](#)

```
=====
ip a
2: lo: <LOOPBACK,UP,LOWER_UP> mtu 16436 qdisc noqueue
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
4: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 100
    link/ether 00:1c:c0:41:84:80 brd ff:ff:ff:ff:ff:ff
    inet 192.168.176.11/24 brd 192.168.176.255 scope global eth0
    inet 192.168.176.12/24 brd 192.168.176.255 scope global secondary eth0:0
    inet6 fe80::21c:c0ff:fe41:8480/64 scope link
        valid_lft forever preferred_lft forever
1: sit0: <NOARP> mtu 1480 qdisc noop
    link/sit 0.0.0.0 brd 0.0.0.0
11: tunl0: <NOARP> mtu 1480 qdisc noop
    link/ipip 0.0.0.0 brd 0.0.0.0
13: venet0: <BROADCAST,POINTOPOINT,NOARP,UP,LOWER_UP> mtu 1500 qdisc noqueue
    link/void
```

```
=====
ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 16436 qdisc noqueue
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
3: venet0: <BROADCAST,POINTOPOINT,NOARP,UP,LOWER_UP> mtu 1500 qdisc noqueue
    link/void
    inet 127.0.0.1/32 scope host venet0
    inet 192.168.176.12/32 brd 192.168.176.12 scope global venet0:0
```

```
=====
ping 213.180.204.8
PING 213.180.204.8 (213.180.204. 56(84) bytes of data.
```

```
--- 213.180.204.8 ping statistics ---
35 packets transmitted, 0 received, 100% packet loss, time 33998ms
```

22:10:56.283829 IP 192.168.176.12 > 213.180.204.8: ICMP echo request, id 37436, seq 5, length 64
22:10:57.283962 IP 192.168.176.12 > 213.180.204.8: ICMP echo request, id 37436, seq 6, length 64
22:10:58.284094 IP 192.168.176.12 > 213.180.204.8: ICMP echo request, id 37436, seq 7, length 64
22:10:59.283228 IP 192.168.176.12 > 213.180.204.8: ICMP echo request, id 37436, seq 8, length 64
=====

