
Subject: Re: ipt_MARK missed?
Posted by [hoppaz](#) on Wed, 22 Apr 2009 17:00:27 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Vasily,

seems that after a long time... I can recycle this thread

I'm running into the same prob.

I like to use MARK within the VE. At the VE0 the module has been loaded and is in use - so it works there...

If I try to use it inside the container:

```
/sbin/iptables -t mangle -I PREROUTING -p tcp -d MYHOST --dport 3690 -j MARK --set-mark 1  
FATAL: Could not load /lib/modules/2.6.27.21-briullov/modules.dep: No such file or directory  
FATAL: Could not load /lib/modules/2.6.27.21-briullov/modules.dep: No such file or directory
```

Yes... I use 2.6.27.21-briullov...

---- sniplet from strace ---

```
open("/lib/iptables/libxt_tcp.so", O_RDONLY) = 3  
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\300\7\0"..., 512) = 512  
fstat64(3, {st_mode=S_IFREG|0644, st_size=9736, ...}) = 0  
mmap2(NULL, 12580, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =  
0xb8036000  
mmap2(0xb8038000, 8192, PROT_READ|PROT_WRITE,  
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1) = 0xb8038000  
close(3) = 0  
mprotect(0xb8038000, 4096, PROT_READ) = 0  
open("/lib/iptables/libxt_MARK.so", O_RDONLY) = 3  
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0@\5\0\000"..., 512) = 512  
fstat64(3, {st_mode=S_IFREG|0644, st_size=5708, ...}) = 0  
mmap2(NULL, 8552, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =  
0xb7edf000  
mmap2(0xb7ee0000, 8192, PROT_READ|PROT_WRITE,  
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0) = 0xb7ee0000  
close(3) = 0  
mprotect(0xb7ee0000, 4096, PROT_READ) = 0  
socket(PF_INET, SOCK_RAW, IPPROTO_RAW) = 3  
open("/proc/sys/kernel/modprobe", O_RDONLY) = 4  
read(4, "/sbin/modprobe\n", 1024) = 15  
close(4) = 0  
clone(child_stack=0, flags=CLONE_CHILD_CLEARTID|CLONE_CHILD_SETTID|SIGCHLD,  
child_tidptr=0xb8056b28) = 2598
```

```
wait4(-1, FATAL: Could not load /lib/modules/2.6.27.21-briullof/modules.dep: No such file or
directory
[{{WIFEXITED(s) && WEXITSTATUS(s) == 1}}, 0, NULL) = 2598
--- SIGCHLD (Child exited) @ 0 (0) ---
getsockopt(3, SOL_IP, 0x43 /* IP_??? */ ,
"MARK\0\t\0Z\205\277\244\20\356\267\=\5\270eH\5\270\240"... , [30]) = 0
close(3) = 0
socket(PF_INET, SOCK_RAW, IPPROTO_RAW) = 3
open("/proc/sys/kernel/modprobe", O_RDONLY) = 4
read(4, "/sbin/modprobe\n", 1024) = 15
close(4) = 0
clone(child_stack=0, flags=CLONE_CHILD_CLEARTID|CLONE_CHILD_SETTID|SIGCHLD,
child_tidptr=0xb8056b28) = 2599
wait4(-1, FATAL: Could not load /lib/modules/2.6.27.21-briullof/modules.dep: No such file or
directory
[{{WIFEXITED(s) && WEXITSTATUS(s) == 1}}, 0, NULL) = 2599
--- SIGCHLD (Child exited) @ 0 (0) ---
getsockopt(3, SOL_IP, 0x43 /* IP_??? */ ,
"MARK\0\t\0Z\205\277\244\20\356\267\=\5\270eH\5\270\240"... , [30]) = 0
close(3) = 0
getpid() = 2597
open("/etc/resolv.conf", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=113, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0xb8035000
read(3, "domain cmi\nsearch cmi"... , 4096) = 113
read(3, "", 4096) = 0
close(3) = 0
munmap(0xb8035000, 4096) = 0
open("/etc/networks", O_RDONLY|0x80000 /* O_??? */) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=91, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0xb8035000
read(3, "# symbolic names for networks, s"... , 4096) = 91
```

---- sniplet from strace ---

Any ideas ?

Lars
