


```
open("/usr/lib/vzctl/lib/sse2/libvzctl.so.0.0.1", O_RDONLY) = -1 ENOENT (No such file or
directory)
open("/usr/lib/vzctl/lib/libvzctl.so.0.0.1", O_RDONLY) = 3
read(3, "\177ELF1\1\1\0\0\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\365"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=400924, ...}) = 0
old_mmap(0x4527b000, 101720, PROT_READ|PROT_EXEC,
MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x4527b000
old_mmap(0x45293000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x18000) = 0x45293000
close(3) = 0
open("/usr/lib/vzctl/lib/tls/i686/sse2/libvzctl-fs.so", O_RDONLY) = -1 ENOENT (No such file or
directory)
open("/usr/lib/vzctl/lib/tls/i686/libvzctl-fs.so", O_RDONLY) = -1 ENOENT (No such file or directory)
open("/usr/lib/vzctl/lib/tls/sse2/libvzctl-fs.so", O_RDONLY) = -1 ENOENT (No such file or
directory)
open("/usr/lib/vzctl/lib/tls/libvzctl-fs.so", O_RDONLY) = -1 ENOENT (No such file or directory)
open("/usr/lib/vzctl/lib/i686/sse2/libvzctl-fs.so", O_RDONLY) = -1 ENOENT (No such file or
directory)
open("/usr/lib/vzctl/lib/i686/libvzctl-fs.so", O_RDONLY) = -1 ENOENT (No such file or directory)
open("/usr/lib/vzctl/lib/sse2/libvzctl-fs.so", O_RDONLY) = -1 ENOENT (No such file or directory)
open("/usr/lib/vzctl/lib/libvzctl-fs.so", O_RDONLY) = 3
read(3, "\177ELF1\1\1\0\0\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0@\x'E4\0"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=26865, ...}) = 0
old_mmap(0x45277000, 7412, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE,
3, 0) = 0x45277000
old_mmap(0x45278000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0) = 0x45278000
close(3) = 0
open("/usr/lib/vzctl/lib/tls/i686/sse2/libutil.so.1", O_RDONLY) = -1 ENOENT (No such file or
directory)
open("/usr/lib/vzctl/lib/tls/i686/libutil.so.1", O_RDONLY) = -1 ENOENT (No such file or directory)
open("/usr/lib/vzctl/lib/tls/sse2/libutil.so.1", O_RDONLY) = -1 ENOENT (No such file or directory)
open("/usr/lib/vzctl/lib/tls/libutil.so.1", O_RDONLY) = -1 ENOENT (No such file or directory)
open("/usr/lib/vzctl/lib/i686/sse2/libutil.so.1", O_RDONLY) = -1 ENOENT (No such file or directory)
open("/usr/lib/vzctl/lib/i686/libutil.so.1", O_RDONLY) = -1 ENOENT (No such file or directory)
open("/usr/lib/vzctl/lib/sse2/libutil.so.1", O_RDONLY) = -1 ENOENT (No such file or directory)
open("/usr/lib/vzctl/lib/libutil.so.1", O_RDONLY) = -1 ENOENT (No such file or directory)
open("/lib/libutil.so.1", O_RDONLY) = 3
read(3, "\177ELF1\1\1\0\0\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\260\267"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=15080, ...}) = 0
old_mmap(0xb75000, 12432, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE,
3, 0) = 0xb75000
old_mmap(0xb77000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1000) = 0xb77000
close(3) = 0
open("/usr/lib/vzctl/lib/tls/i686/sse2/libc.so.6", O_RDONLY) = -1 ENOENT (No such file or
directory)
open("/usr/lib/vzctl/lib/tls/i686/libc.so.6", O_RDONLY) = -1 ENOENT (No such file or directory)
```



```

mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x40001000
read(4, "# This is an example configurati"..., 4096) = 1420
read(4, "", 4096) = 0
close(4) = 0
munmap(0x40001000, 4096) = 0
open("/dev/vzctl", O_RDWR) = 4
ioctl(4, 0x400c2e05, 0xbfffe1e0) = 0
close(3) = 0
munmap(0x40000000, 4096) = 0
ioctl(4, 0x400c2e05, 0xbfffe1d0) = 0
pipe([3, 5]) = 0
pipe([6, 7]) = 0
pipe([8, 9]) = 0
syscall_511(0x6978, 0x40006cd0, 0x40006cc0, 0xc, 0x804f758, 0xbfffe218, 0xfffffda, 0x7b,
0x7b, 0, 0x33, 0x1ff, 0x9ff7e2, 0x73, 0x206, 0xbfffe038, 0x7b, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0) = 0
socket(PF_FILE, SOCK_STREAM, 0) = 10
fcntl64(10, F_GETFL) = 0x2 (flags O_RDWR)
fcntl64(10, F_SETFL, O_RDWR|O_NONBLOCK) = 0
connect(10, {sa_family=AF_FILE, path="/var/run/nscd/socket"}, 110) = -1 ENOENT (No such file
or directory)
close(10) = 0
socket(PF_FILE, SOCK_STREAM, 0) = 10
fcntl64(10, F_GETFL) = 0x2 (flags O_RDWR)
fcntl64(10, F_SETFL, O_RDWR|O_NONBLOCK) = 0
connect(10, {sa_family=AF_FILE, path="/var/run/nscd/socket"}, 110) = -1 ENOENT (No such file
or directory)
close(10) = 0
open("/etc/nsswitch.conf", O_RDONLY) = 10
fstat64(10, {st_mode=S_IFREG|0644, st_size=1686, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x40000000
read(10, "#\n# /etc/nsswitch.conf\n#\n# An ex"..., 4096) = 1686
read(10, "", 4096) = 0
close(10) = 0
munmap(0x40000000, 4096) = 0
open("/usr/lib/vzctl/lib/tls/i686/sse2/libnss_files.so.2", O_RDONLY) = -1 ENOENT (No such file or
directory)
open("/usr/lib/vzctl/lib/tls/i686/libnss_files.so.2", O_RDONLY) = -1 ENOENT (No such file or
directory)
open("/usr/lib/vzctl/lib/tls/sse2/libnss_files.so.2", O_RDONLY) = -1 ENOENT (No such file or
directory)
open("/usr/lib/vzctl/lib/tls/libnss_files.so.2", O_RDONLY) = -1 ENOENT (No such file or directory)
open("/usr/lib/vzctl/lib/i686/sse2/libnss_files.so.2", O_RDONLY) = -1 ENOENT (No such file or
directory)
open("/usr/lib/vzctl/lib/i686/libnss_files.so.2", O_RDONLY) = -1 ENOENT (No such file or
directory)

```

```
open("/usr/lib/vzctl/lib/libnss_files.so.2", O_RDONLY) = -1 ENOENT (No such file or
directory)
open("/usr/lib/vzctl/lib/libnss_files.so.2", O_RDONLY) = -1 ENOENT (No such file or directory)
open("/etc/ld.so.cache", O_RDONLY) = 10
fstat64(10, {st_mode=S_IFREG|0644, st_size=23577, ...}) = 0
old_mmap(NULL, 23577, PROT_READ, MAP_PRIVATE, 10, 0) = 0x40000000
close(10) = 0
open("/lib/libnss_files.so.2", O_RDONLY) = 10
read(10, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0 \33\0\000"..., 512) = 512
fstat64(10, {st_mode=S_IFREG|0755, st_size=46552, ...}) = 0
old_mmap(NULL, 41616, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 10,
0) = 0x40009000
old_mmap(0x40012000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 10, 0x8000) = 0x40012000
close(10) = 0
mprotect(0x40012000, 4096, PROT_READ) = 0
munmap(0x40000000, 23577) = 0
open("/etc/passwd", O_RDONLY) = 10
fcntl64(10, F_GETFD) = 0
fcntl64(10, F_SETFD, FD_CLOEXEC) = 0
fstat64(10, {st_mode=S_IFREG|0644, st_size=1539, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x40000000
read(10, "root:x:0:0:root:/root:/bin/bash\n"..., 4096) = 1539
close(10) = 0
munmap(0x40000000, 4096) = 0
socket(PF_FILE, SOCK_STREAM, 0) = 10
fcntl64(10, F_GETFL) = 0x2 (flags O_RDWR)
fcntl64(10, F_SETFL, O_RDWR|O_NONBLOCK) = 0
connect(10, {sa_family=AF_FILE, path="/var/run/nscd/socket"}, 110) = -1 ENOENT (No such file
or directory)
close(10) = 0
socket(PF_FILE, SOCK_STREAM, 0) = 10
fcntl64(10, F_GETFL) = 0x2 (flags O_RDWR)
fcntl64(10, F_SETFL, O_RDWR|O_NONBLOCK) = 0
connect(10, {sa_family=AF_FILE, path="/var/run/nscd/socket"}, 110) = -1 ENOENT (No such file
or directory)
close(10) = 0
open("/etc/group", O_RDONLY) = 10
fcntl64(10, F_GETFD) = 0
fcntl64(10, F_SETFD, FD_CLOEXEC) = 0
fstat64(10, {st_mode=S_IFREG|0644, st_size=608, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x40000000
read(10, "root:x:0:root\nbin:x:1:root,bin,d"..., 4096) = 608
close(10) = 0
munmap(0x40000000, 4096) = 0
rt_sigaction(SIGCHLD, {0x804c140, [], SA_RESTORER|SA_NOCLDSTOP, 0xa452d8}, NULL, =
```

```
0
rt_sigaction(SIGPIPE, {SIG_IGN}, NULL, 0) = 0
clone(child_stack=0, flags=CLONE_CHILD_CLEARTID|CLONE_CHILD_SETTID|SIGCHLD,
child_tidptr=0x40007ba8) = 2729
close(3) = 0
close(7) = 0
close(9) = 0
read(8, "\377\377\377\377", 4) = 4
fstat64(1, {st_mode=S_IFCHR|0620, st_rdev=makedev(136, 3), ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x40000000
write(1, "enter failed\n", 13) = 13
--- SIGCHLD (Child exited) @ 0 (0) ---
sigreturn() = ? (mask now [])
waitpid(2729, [{WIFEXITED(s) && WEXITSTATUS(s) == 255}], 0) = 2729
close(5) = 0
close(6) = 0
close(4) = 0
munmap(0x40000000, 4096) = 0
exit_group(0) = ?
```
