
Posted by [lithium](#) on Mon, 09 Nov 2009 08:04:17 GMT

[View Forum Message](#) <> [Reply to Message](#)

Oct 23 19:13:03 Updated: initscripts-8.45.30-2.el5.centos.i386

```
--- rc.sysinit.rpmsave 2009-08-24 14:41:32.000000000 +0400
+++ rc.sysinit 2009-09-29 03:34:29.000000000 +0400
@@ -343,7 +343,7 @@
nashpid=$(pidof nash 2>/dev/null)
[ -n "$nashpid" ] && kill $nashpid >/dev/null 2>&1
unset nashpid
-
+ /sbin/start_udev

# Load other user-defined modules
for file in /etc/sysconfig/modules/*.modules ; do
@@ -761,9 +761,9 @@
# mounted). Contrary to standard usage,
# filesystems are NOT unmounted in single user mode.
if [ "$READONLY" != "yes" ] ; then
-   action $"Mounting local filesystems: " mount -a -t nonfs,nfs4,smbfs,ncpfs,cifs,gfs -O
no_netdev
+   action $"Mounting local filesystems: " mount -a -t nonfs,nfs4,smbfs,ncpfs,cifs,gfs,gfs2 -O
no_netdev
else
```

```

-    action $"Mounting local filesystems: " mount -a -n -t nfs4,smbfs,ncpfs,cifs,gfs -O no_netdev
+    action $"Mounting local filesystems: " mount -a -n -t nfs4,smbfs,ncpfs,cifs,gfs,gfs2 -O
no_netdev
fi

if [ -x /sbin/quotaon ]; then
@@ -851,7 +851,7 @@

# Clean out /.
rm -f /fastboot /fsckoptions /forcefsck /.autofsck /forcequotacheck /halt \
-    /poweroff &> /dev/null
+    /poweroff /.suspended &> /dev/null

# Do we need (w|u)tmpx files? We don't set them up, but the sysadmin might...
_NEED_XFILES=
@@ -869,6 +869,7 @@
    */cvs)      rm -rf $afile/* ;;
    */dovecot)  rm -f $afile/*/* ;;
    */cups)     rm -f $afile/*/* ;;
+    */libvirt) rm -rf $afile/*/* ;;
    *)         rm -f $afile/* ;;
esac
else

```