
Subject: Re: running cobbler inside a CT
Posted by [olojoh1977](#) on Sat, 24 Jul 2010 08:45:06 GMT
[View Forum Message](#) <> [Reply to Message](#)

Unfortunately my problem didnt go away after restarting httpd.

Perhaps I have some faulty configuration? Plz check.

I'm running a CT with CentOS 4.8 (precreated template) with veth-interface.

On CT0 eth0 and veth103.0 is up and running.

Inside CT103:

```
bash> cat /etc/sysconfig/network-scripts/ifcfg-eth0
```

```
DEVICE=eth0
```

```
ONBOOT=yes
```

```
BOOTPROTO=static
```

```
IPADDR=10.213.223.103
```

```
NETMASK=255.255.255.0
```

```
GATEWAY=10.213.223.1
```

Snippet from CT0's /etc/sysctl.conf

```
net.ipv4.conf.eth0.forwarding = 1
```

```
net.ipv4.conf.eth0.proxy_arp = 1
```

```
# commented rows below because it's taken care of in mount-script
```

```
#net.ipv4.conf.veth103.0.forwarding = 1
```

```
#net.ipv4.conf.veth103.0.proxy_arp = 1
```

My 103.conf is created from basic-sample, just added veth-interface.

Appending /etc/vz/conf/103.conf and /etc/vz/conf/103.mount for the sake of clarity.

File Attachments

1) [103.conf](#), downloaded 359 times

2) [103.mount.txt](#), downloaded 392 times
