

---

Subject: [PATCH 2/2] c/r: Check for bound AF\_UNIX sockets before doing unlink()  
Posted by [Dan Smith](#) on Mon, 07 Feb 2011 16:42:59 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

If we're not restarting inside our own network namespace, the explicit unlink() of the AF\_UNIX socket path before binding is not safe. This could end up hosing something that has that socket open. The easiest way to encounter such a problem is to checkpoint and restart an application with a connection to syslogd. Without this patch, on restart you hose the system syslogd by unlink()'ing its /dev/log.

We hold the mutex on the parent inode to make sure that we don't race with another unix\_bind() in progress.

Signed-off-by: Dan Smith <danms@us.ibm.com>

```
---  
include/net/af_unix.h | 1 +  
net/unix/af_unix.c | 2 +-  
net/unix/checkpoint.c | 55 ++++++-----  
3 files changed, 28 insertions(+), 30 deletions(-)
```

```
diff --git a/include/net/af_unix.h b/include/net/af_unix.h  
index add734f..a24a842 100644  
--- a/include/net/af_unix.h  
+++ b/include/net/af_unix.h  
@@ -11,6 +11,7 @@ extern void unix_notinflight(struct file *fp);  
extern void unix_gc(void);  
extern void wait_for_unix_gc(void);  
extern struct sock *unix_get_socket(struct file *filp);  
+extern struct sock *unix_find_socket_byinode(struct inode *i);  
  
#define UNIX_HASH_SIZE 256
```

```
diff --git a/net/unix/af_unix.c b/net/unix/af_unix.c  
index cb7afd5..e385a1e 100644  
--- a/net/unix/af_unix.c  
+++ b/net/unix/af_unix.c  
@@ -282,7 +282,7 @@ static inline struct sock *unix_find_socket_byname(struct net *net,  
    return s;  
}
```

```
-static struct sock *unix_find_socket_byinode(struct inode *i)  
+struct sock *unix_find_socket_byinode(struct inode *i)  
{  
    struct sock *s;  
    struct hlist_node *node;
```

```
diff --git a/net/unix/checkpoint.c b/net/unix/checkpoint.c  
index 25464cc..0a06c94 100644
```

```

--- a/net/unix/checkpoint.c
+++ b/net/unix/checkpoint.c
@@ -467,38 +467,32 @@ static int unix_restore_connected(struct ckpt_ctx *ctx,
    return ret;
}

-static int unix_unlink(const char *name)
+/**
+ * Perform the unlink() operation of a hopefully-stale unix socket.
+ * We should, however, first determine that a socket is not already
+ * bound there. If not, we can unlink() while holding the parent's
+ * inode mutex to make sure that we don't race with bind().
+ */
+static int unix_unlink(struct path *parent, const char *name)
{
- struct path spath;
- struct path ppath;
- int ret;
+ int ret = -EADDRINUSE;
+ struct sock *sk;
+ struct path path;

- ret = kern_path(name, 0, &spath);
+ ret = kern_path(name, LOOKUP_OPEN, &path);
  if (ret)
- return ret;
+ return 0; /* Not found is a good thing! */

- ret = kern_path(name, LOOKUP_PARENT, &ppath);
- if (ret)
- goto out_s;
+ mutex_lock(&parent->dentry->d_inode->i_mutex);

- if (!spath.dentry) {
- ckpt_debug("No dentry found for %s\n", name);
- ret = -ENOENT;
- goto out_p;
- }
-
- if (!ppath.dentry || !ppath.dentry->d_inode) {
- ckpt_debug("No inode for parent of %s\n", name);
- ret = -ENOENT;
- goto out_p;
- }
-
- ret = vfs_unlink(ppath.dentry->d_inode, spath.dentry);
- out_p:
- path_put(&ppath);

```

```

- out_s:
- path_put(&spath);
+ sk = unix_find_socket_byinode(path.dentry->d_inode);
+ if (sk)
+ sock_put(sk);
+ else
+ ret = vfs_unlink(parent->dentry->d_inode, path.dentry);

+ mutex_unlock(&parent->dentry->d_inode->i_mutex);
+ path_put(&spath);
  return ret;
}

@@ -531,9 +525,13 @@ static int unix_chdir_and_bind(struct socket *sock,
    cur = current->fs->pwd;
    current->fs->pwd = dir;
    spin_unlock(&current->fs->lock);
+ } else {
+ ret = kern_path(un->sun_path, LOOKUP_PARENT, &dir);
+ if (ret)
+ return ret;
  }

- ret = unix_unlink(un->sun_path);
+ ret = unix_unlink(&dir, un->sun_path);
  ckpt_debug("unlink(%s): %i\n", un->sun_path, ret);
  if ((ret == 0) || (ret == -ENOENT))
    ret = sock_bind(sock, addr, addrlen);
@@ -544,8 +542,7 @@ static int unix_chdir_and_bind(struct socket *sock,
    spin_unlock(&current->fs->lock);
  }
  out:
- if (path)
- path_put(&dir);
+ path_put(&dir);

  return ret;
}
--
1.7.2.2

```

---

Containers mailing list  
Containers@lists.linux-foundation.org  
<https://lists.linux-foundation.org/mailman/listinfo/containers>

---