
Subject: [PATCH 02/11] restart: cleanup setup/cleanup of freezer cgroups
Posted by [Oren Laadan](#) on Mon, 07 Feb 2011 17:21:23 GMT

[View Forum Message](#) <> [Reply to Message](#)

Signed-off-by: Oren Laadan <orenl@cs.columbia.edu>

restart.c | 22 ++++++-----
1 files changed, 10 insertions(+), 12 deletions(-)

```
diff --git a/restart.c b/restart.c
index 8106fd6..195a892 100644
--- a/restart.c
+++ b/restart.c
@@ -359,35 +359,32 @@ static void sigint_handler(int sig)

static int freezer_prepare(struct ckpt_ctx *ctx)
{
- char *freezer;
    int fd, ret;

#define FREEZER_THAWED "THAWED"

- freezer = malloc(strlen(ctx->args->freezer) + 32);
- if (!freezer) {
+ ctx->freezer = malloc(strlen(ctx->args->freezer) + 32);
+ if (!ctx->freezer) {
    ckpt_perror("malloc freezer buf");
- return -1;
+ return ctx_set_errno(ctx);
}

- sprintf(freezer, "%s/freezer.state", ctx->args->freezer);
+ sprintf(ctx->freezer, "%s/freezer.state", ctx->args->freezer);

- fd = open(freezer, O_WRONLY, 0);
+ fd = open(ctx->freezer, O_WRONLY, 0);
if (fd < 0) {
    ckpt_perror("freezer path");
- free(freezer);
- return -1;
+ return ctx_set_errno(ctx);
}
ret = write(fd, FREEZER_THAWED, sizeof(FREEZER_THAWED));
if (ret != sizeof(FREEZER_THAWED)) {
    ckpt_perror("thawing freezer");
- free(freezer);
+ ctx_set_errno(ctx);
close(fd);
```

```

    return -1;
}

- sprintf(freezer, "%s/tasks", ctx->args->freezer);
- ctx->freezer = freezer;
+ sprintf(ctx->freezer, "%s/tasks", ctx->args->freezer);
close(fd);
return 0;
}
@@ -400,13 +397,14 @@ static int freezer_register(struct ckpt_ctx *ctx, pid_t pid)
fd = open(ctx->freezer, O_WRONLY, 0);
if (fd < 0) {
ckpt_perror("freezer path");
- return -1;
+ return ctx_set_errno(ctx);
}

n = sprintf(pidstr, "%d", pid);
ret = write(fd, pidstr, n);
if (ret != n) {
ckpt_perror("adding pid %d to freezer");
+ ctx_set_errno(ctx);
close(fd);
return -1;
}
--
```

1.7.1

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
