

---

Subject: [PATCH 3/9] allow sethostname in a container  
Posted by [serge](#) on Thu, 17 Feb 2011 15:03:16 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Signed-off-by: Serge E. Hallyn <[serge.hallyn@canonical.com](mailto:serge.hallyn@canonical.com)>

---

kernel/sys.c | 2 +-  
1 files changed, 1 insertions(+), 1 deletions(-)

```
diff --git a/kernel/sys.c b/kernel/sys.c
index 18da702..7a1bbad 100644
--- a/kernel/sys.c
+++ b/kernel/sys.c
@@ -1177,7 +1177,7 @@ SYSCALL_DEFINE2(sethostname, char __user *, name, int, len)
 int errno;
 char tmp[__NEW_UTS_LEN];

- if (!capable(CAP_SYS_ADMIN))
+ if (!ns_capable(current->nsproxy->uts_ns->user_ns, CAP_SYS_ADMIN))
    return -EPERM;
 if (len < 0 || len > __NEW_UTS_LEN)
    return -EINVAL;
```

--

1.7.0.4

---

Containers mailing list

[Containers@lists.linux-foundation.org](mailto:Containers@lists.linux-foundation.org)

<https://lists.linux-foundation.org/mailman/listinfo/containers>

---