

---

Subject: [PATCH 3/9] allow sethostname in a container

Posted by [serge](#) on Thu, 17 Feb 2011 15:03:16 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Signed-off-by: Serge E. Hallyn <serge.hallyn@canonical.com>

---

kernel/sys.c | 2 +-  
1 files changed, 1 insertions(+), 1 deletions(-)

diff --git a/kernel/sys.c b/kernel/sys.c

index 18da702..7a1bbad 100644

--- a/kernel/sys.c

+++ b/kernel/sys.c

```
@@ -1177,7 +1177,7 @@ SYSCALL_DEFINE2(sethostname, char __user *, name, int, len)
    int errno;
    char tmp[__NEW_UTS_LEN];
```

```
- if (!capable(CAP_SYS_ADMIN))
```

```
+ if (!ns_capable(current->nsproxy->uts_ns->user_ns, CAP_SYS_ADMIN))
```

```
    return -EPERM;
```

```
    if (len < 0 || len > __NEW_UTS_LEN)
```

```
        return -EINVAL;
```

```
--
```

1.7.0.4

---

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>

---