
Subject: Re: [PATCH 4/9] allow killing tasks in your own or child userns
Posted by [ebiederm](#) on Fri, 18 Feb 2011 03:00:44 GMT
[View Forum Message](#) <> [Reply to Message](#)

"Serge E. Hallyn" <serge@hallyn.com> writes:

> Changelog:
> Dec 8: Fixed bug in my check_kill_permission pointed out by
> Eric Biederman.
> Dec 13: Apply Eric's suggestion to pass target task into kill_ok_by_cred()
> for clarity
> Dec 31: address comment by Eric Biederman:
> don't need cred/tcred in check_kill_permission.
> Jan 1: use const cred struct.
> Jan 11: Per Bastian Blank's advice, clean up kill_ok_by_cred().
> Feb 16: kill_ok_by_cred: fix bad parentheses

Acked-by: "Eric W. Biederman" <ebiederm@xmission.com>

>
> Signed-off-by: Serge E. Hallyn <serge.hallyn@canonical.com>
> ---
> kernel/signal.c | 30 ++++++-----
> 1 files changed, 22 insertions(+), 8 deletions(-)
>
> diff --git a/kernel/signal.c b/kernel/signal.c
> index 4e3cff1..ffe4bdf 100644
> --- a/kernel/signal.c
> +++ b/kernel/signal.c
> @@ -636,13 +636,33 @@ static inline bool si_fromuser(const struct siginfo *info)
> }
>
> /*
> + * called with RCU read lock from check_kill_permission()
> + */
> +static inline int kill_ok_by_cred(struct task_struct *t)
> +{
> + const struct cred *cred = current_cred();
> + const struct cred *tcred = __task_cred(t);
> +
> + if (cred->user->user_ns == tcred->user->user_ns &&
> + (cred->euid == tcred->suid ||
> + cred->euid == tcred->uid ||
> + cred->uid == tcred->suid ||
> + cred->uid == tcred->uid))
> + return 1;
> +
> + if (ns_capable(tcred->user->user_ns, CAP_KILL))

```

> + return 1;
> +
> + return 0;
> +}
> +
> +/*
>  * Bad permissions for sending the signal
>  * - the caller must hold the RCU read lock
>  */
> static int check_kill_permission(int sig, struct siginfo *info,
>     struct task_struct *t)
> {
> - const struct cred *cred, *tcred;
>   struct pid *sid;
>   int error;
>
> @@ -656,14 +676,8 @@ static int check_kill_permission(int sig, struct siginfo *info,
>   if (error)
>       return error;
>
> - cred = current_cred();
> - tcred = __task_cred(t);
>   if (!same_thread_group(current, t) &&
>       (cred->euid ^ tcred->suid) &&
>       (cred->euid ^ tcred->uid) &&
>       (cred->uid ^ tcred->suid) &&
>       (cred->uid ^ tcred->uid) &&
>       !capable(CAP_KILL)) {
> +   !kill_ok_by_cred(t)) {
>     switch (sig) {
>     case SIGCONT:
>       sid = task_session(t);

```

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
