
Subject: Re: [PATCH 3/9] allow sethostname in a container
Posted by [ebiederm](#) on Fri, 18 Feb 2011 03:05:21 GMT

[View Forum Message](#) <> [Reply to Message](#)

"Serge E. Hallyn" <serge@hallyn.com> writes:

Acked-by: "Eric W. Biederman" <ebiederm@xmission.com>

```
> Signed-off-by: Serge E. Hallyn <serge.hallyn@canonical.com>
> ---
> kernel/sys.c | 2 ++
> 1 files changed, 1 insertions(+), 1 deletions(-)
>
> diff --git a/kernel/sys.c b/kernel/sys.c
> index 18da702..7a1bbad 100644
> --- a/kernel/sys.c
> +++ b/kernel/sys.c
> @@ -1177,7 +1177,7 @@ SYSCALL_DEFINE2(sethostname, char __user *, name, int, len)
>     int errno;
>     char tmp[__NEW_UTS_LEN];
>
> - if (!capable(CAP_SYS_ADMIN))
> + if (!ns_capable(current->nsproxy->uts_ns->user_ns, CAP_SYS_ADMIN))
>     return -EPERM;
>     if (len < 0 || len > __NEW_UTS_LEN)
>     return -EINVAL;
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
