
Subject: Re: [PATCH 3/9] allow sethostname in a container

Posted by [ebiederm](#) on Fri, 18 Feb 2011 03:05:21 GMT

[View Forum Message](#) <> [Reply to Message](#)

"Serge E. Hallyn" <serge@hallyn.com> writes:

Acked-by: "Eric W. Biederman" <ebiederm@xmission.com>

> Signed-off-by: Serge E. Hallyn <serge.hallyn@canonical.com>

> ---

> kernel/sys.c | 2 +-

> 1 files changed, 1 insertions(+), 1 deletions(-)

>

> diff --git a/kernel/sys.c b/kernel/sys.c

> index 18da702..7a1bbad 100644

> --- a/kernel/sys.c

> +++ b/kernel/sys.c

> @@ -1177,7 +1177,7 @@ SYSCALL_DEFINE2(sethostname, char __user *, name, int, len)

> int errno;

> char tmp[__NEW_UTS_LEN];

>

> - if (!capable(CAP_SYS_ADMIN))

> + if (!ns_capable(current->nsproxy->uts_ns->user_ns, CAP_SYS_ADMIN))

> return -EPERM;

> if (len < 0 || len > __NEW_UTS_LEN)

> return -EINVAL;

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
