

---

Subject: Re: [PATCH v4 06/11] memcg: add dirty page accounting infrastructure  
Posted by [Wu Fengguang](#) on Fri, 29 Oct 2010 11:13:00 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

On Fri, Oct 29, 2010 at 03:09:09PM +0800, Greg Thelen wrote:

```
> +  
> + case MEMCG_NR_FILE_DIRTY:  
> + /* Use Test{Set,Clear} to only un/charge the memcg once. */  
> + if (val > 0) {  
> +   if (TestSetPageCgroupFileDirty(pc))  
> +     val = 0;  
> + } else {  
> +   if (!TestClearPageCgroupFileDirty(pc))  
> +     val = 0;  
> + }
```

I'm wondering why TestSet/TestClear and even the cgroup page flags for dirty/writeback/unstable pages are necessary at all (it helps to document in changelog if there are any). For example, VFS will call TestSetPageDirty() before calling mem\_cgroup\_inc\_page\_stat(MEMCG\_NR\_FILE\_DIRTY), so there should be no chance of false double counting.

Thanks,  
Fengguang

---

Containers mailing list  
[Containers@lists.linux-foundation.org](mailto:Containers@lists.linux-foundation.org)  
<https://lists.linux-foundation.org/mailman/listinfo/containers>

---