
Subject: [PATCH v3 10/16] nfs: per-rpc_pipefs dns cache
Posted by [Kirill A. Shutemov](#) on Fri, 14 Jan 2011 13:49:08 GMT
[View Forum Message](#) <> [Reply to Message](#)

Lazy initialization of dns cache: on first call nfs_dns_resolve_name().
Every rpc_pipefs has separate dns cache now.

Signed-off-by: Kirill A. Shutemov <kas@openvz.org>

fs/nfs/cache_lib.c | 17 ++-----
fs/nfs/cache_lib.h | 3 +-
fs/nfs/dns_resolve.c | 137 ++++++++++++++++++++++++++++++++++++++-----
fs/nfs/dns_resolve.h | 15 +-----
fs/nfs/inode.c | 9 +---
fs/nfs/nfs4namespace.c | 4 +-
6 files changed, 117 insertions(+), 68 deletions(-)

diff --git a/fs/nfs/cache_lib.c b/fs/nfs/cache_lib.c
index 0944d4e..9b99d9e 100644

--- a/fs/nfs/cache_lib.c
+++ b/fs/nfs/cache_lib.c

@@ -12,7 +12,6 @@

#include <linux/namei.h>
#include <linux/slab.h>
#include <linux/sunrpc/cache.h>
-#include <linux/sunrpc/rpc_pipe_fs.h>

#include "cache_lib.h"

@@ -111,25 +110,17 @@ int nfs_cache_wait_for_upcall(struct nfs_cache_defer_req *dreq)
return 0;
}

-int nfs_cache_register(struct cache_detail *cd)
+int nfs_cache_register(struct cache_detail *cd, struct vfsmount *rpcmount)
{
struct nameidata nd;
- struct vfsmount *mnt;
int ret;

- mnt = mntget(init_rpc_pipefs);
- if (IS_ERR(mnt))
- return PTR_ERR(mnt);
- ret = vfs_path_lookup(mnt->mnt_root, mnt, "/cache", 0, &nd);
+ ret = vfs_path_lookup(rpcmount->mnt_root, rpcmount, "/cache", 0, &nd);
if (ret)
- goto err;
- ret = sunrpc_cache_register_pipefs(mnt, nd.path.dentry,

```

+ return ret;
+ ret = sunrpc_cache_register_pipefs(rpcmount, nd.path.dentry,
    cd->name, 0600, cd);
    path_put(&nd.path);
- if (!ret)
- return ret;
-err:
- mntput(mnt);
    return ret;
}

```

diff --git a/fs/nfs/cache_lib.h b/fs/nfs/cache_lib.h

index 76f856e..1d4a0a5 100644

--- a/fs/nfs/cache_lib.h

+++ b/fs/nfs/cache_lib.h

```

@@ -23,5 +23,6 @@ extern struct nfs_cache_defer_req *nfs_cache_defer_req_alloc(void);
extern void nfs_cache_defer_req_put(struct nfs_cache_defer_req *dreq);
extern int nfs_cache_wait_for_upcall(struct nfs_cache_defer_req *dreq);

```

```

-extern int nfs_cache_register(struct cache_detail *cd);
+extern int nfs_cache_register(struct cache_detail *cd,
+ struct vfsmount *rpcmount);
extern void nfs_cache_unregister(struct cache_detail *cd);

```

diff --git a/fs/nfs/dns_resolve.c b/fs/nfs/dns_resolve.c

index a6e711a..a832e64 100644

--- a/fs/nfs/dns_resolve.c

+++ b/fs/nfs/dns_resolve.c

```

@@ -12,7 +12,7 @@

```

```

#include <linux/dns_resolver.h>

```

```

ssize_t nfs_dns_resolve_name(char *name, size_t namelen,
- struct sockaddr *sa, size_t salen)
+ struct sockaddr *sa, size_t salen, struct vfsmount *rpcmount)
{

```

```

    ssize_t ret;
    char *ip_addr = NULL;
@@ -37,9 +37,11 @@ ssize_t nfs_dns_resolve_name(char *name, size_t namelen,
#include <linux/socket.h>
#include <linux/seq_file.h>
#include <linux/inet.h>
+#include <linux/mount.h>
#include <linux/sunrpc/clnt.h>
#include <linux/sunrpc/cache.h>
#include <linux/sunrpc/svcauth.h>
+#include <linux/sunrpc/rpc_pipe_fs.h>

```

```

#include "dns_resolve.h"
#include "cache_lib.h"

```

```

@@ -47,7 +49,13 @@ ssize_t nfs_dns_resolve_name(char *name, size_t namelen,
#define NFS_DNS_HASHBITS 4
#define NFS_DNS_HASHTBL_SIZE (1 << NFS_DNS_HASHBITS)

-static struct cache_head *nfs_dns_table[NFS_DNS_HASHTBL_SIZE];
+static DEFINE_SPINLOCK(nfs_dns_resolve_lock);
+static LIST_HEAD(nfs_dns_resolve_list);
+
+struct nfs_dns_resolve_list {
+ struct list_head list;
+ struct cache_detail *cd;
+};

struct nfs_dns_ent {
    struct cache_head h;
@@ -259,21 +267,6 @@ out:
    return ret;
}

-static struct cache_detail nfs_dns_resolve = {
- .owner = THIS_MODULE,
- .hash_size = NFS_DNS_HASHTBL_SIZE,
- .hash_table = nfs_dns_table,
- .name = "dns_resolve",
- .cache_put = nfs_dns_ent_put,
- .cache_upcall = nfs_dns_upcall,
- .cache_parse = nfs_dns_parse,
- .cache_show = nfs_dns_show,
- .match = nfs_dns_match,
- .init = nfs_dns_ent_init,
- .update = nfs_dns_ent_update,
- .alloc = nfs_dns_ent_alloc,
-};
-
static int do_cache_lookup(struct cache_detail *cd,
    struct nfs_dns_ent *key,
    struct nfs_dns_ent **item,
@@ -336,37 +329,119 @@ out:
    return ret;
}

+static struct cache_detail *nfs_alloc_dns_resolve(void)
+{
+ struct cache_detail *dns_resolve;
+ struct cache_head **hash_table;
+
+ dns_resolve = kmalloc(sizeof(*dns_resolve), GFP_KERNEL);
+ if (!dns_resolve)

```

```

+ return NULL;
+
+ hash_table = kmalloc(sizeof(*hash_table) * NFS_DNS_HASHTBL_SIZE,
+ GFP_KERNEL);
+ if (!hash_table) {
+ kfree(dns_resolve);
+ return NULL;
+ }
+
+ dns_resolve->owner = THIS_MODULE;
+ dns_resolve->hash_size = NFS_DNS_HASHTBL_SIZE;
+ dns_resolve->hash_table = hash_table;
+ dns_resolve->name = "dns_resolve";
+ dns_resolve->cache_put = nfs_dns_ent_put;
+ dns_resolve->cache_upcall = nfs_dns_upcall;
+ dns_resolve->cache_parse = nfs_dns_parse;
+ dns_resolve->cache_show = nfs_dns_show;
+ dns_resolve->match = nfs_dns_match;
+ dns_resolve->init = nfs_dns_ent_init;
+ dns_resolve->update = nfs_dns_ent_update;
+ dns_resolve->alloc = nfs_dns_ent_alloc;
+
+ return dns_resolve;
+}
+
+static void nfs_free_dns_resolve(struct cache_detail *dns_resolve)
+{
+ kfree(dns_resolve->hash_table);
+ kfree(dns_resolve);
+}
+
+static struct cache_detail *nfs_get_dns_resolve(struct vfsmount *rpcmount)
+{
+ struct nfs_dns_resolve_list *dns_resolve;
+ int error = 0;
+
+ spin_lock(&nfs_dns_resolve_lock);
+ list_for_each_entry(dns_resolve, &nfs_dns_resolve_list, list) {
+ if (dns_resolve->cd->u.pipefs.mnt->mnt_sb != rpcmount->mnt_sb)
+ continue;
+
+ spin_unlock(&nfs_dns_resolve_lock);
+ return dns_resolve->cd;
+ }
+
+ dns_resolve = kmalloc(sizeof(*dns_resolve), GFP_KERNEL);
+ if (dns_resolve)
+ dns_resolve->cd = nfs_alloc_dns_resolve();

```

```

+ if (!dns_resolve || !dns_resolve->cd) {
+   error = -ENOMEM;
+   goto err;
+ }
+
+ error = nfs_cache_register(dns_resolve->cd, rpcmount);
+ if (error)
+   goto err;
+
+ INIT_LIST_HEAD(&dns_resolve->list);
+ list_add(&dns_resolve->list, &nfs_dns_resolve_list);
+ spin_unlock(&nfs_dns_resolve_lock);
+
+ return dns_resolve->cd;
+err:
+ spin_unlock(&nfs_dns_resolve_lock);
+ if (dns_resolve)
+   kfree(dns_resolve->cd);
+ kfree(dns_resolve);
+ return dns_resolve->cd;
+}
+
+static void nfs_dns_resolver_destroy(void *data)
+{
+ struct nfs_dns_resolve_list *dns_resolve = data;
+
+ spin_lock(&nfs_dns_resolve_lock);
+ nfs_cache_unregister(dns_resolve->cd);
+ nfs_free_dns_resolve(dns_resolve->cd);
+ list_del(&dns_resolve->list);
+ kfree(dns_resolve);
+ spin_unlock(&nfs_dns_resolve_lock);
+}
+
+ ssize_t nfs_dns_resolve_name(char *name, size_t namelen,
- struct sockaddr *sa, size_t salen)
+ struct sockaddr *sa, size_t salen, struct vfsmount *rpcmount)
+ {
+   struct nfs_dns_ent key = {
+     .hostname = name,
+     .namelen = namelen,
+   };
+ struct cache_detail *dns_resolve;
+ struct nfs_dns_ent *item = NULL;
+ ssize_t ret;

- ret = do_cache_lookup_wait(&nfs_dns_resolve, &key, &item);
+ dns_resolve = nfs_get_dns_resolve(rpcmount);

```

```

+ ret = do_cache_lookup_wait(dns_resolve, &key, &item);
  if (ret == 0) {
    if (salen >= item->addrlen) {
      memcpy(sa, &item->addr, item->addrlen);
      ret = item->addrlen;
    } else
      ret = -EOVERFLOW;
-   cache_put(&item->h, &nfs_dns_resolve);
+   cache_put(&item->h, dns_resolve);
+   rpc_pipefs_add_destroy_cb(rpcmount->mnt_sb,
+   nfs_dns_resolver_destroy, dns_resolve);
  } else if (ret == -ENOENT)
    ret = -ESRCH;
  return ret;
}
-
-int nfs_dns_resolver_init(void)
-{
- return nfs_cache_register(&nfs_dns_resolve);
-}
-
-void nfs_dns_resolver_destroy(void)
-{
- nfs_cache_unregister(&nfs_dns_resolve);
-}
-
-#endif
diff --git a/fs/nfs/dns_resolve.h b/fs/nfs/dns_resolve.h
index 199bb55..74ade60 100644
--- a/fs/nfs/dns_resolve.h
+++ b/fs/nfs/dns_resolve.h
@@ -7,20 +7,7 @@ @@
#define NFS_DNS_HOSTNAME_MAXLEN (128)

-#ifndef CONFIG_NFS_USE_KERNEL_DNS
-static inline int nfs_dns_resolver_init(void)
-{
- return 0;
-}
-
-static inline void nfs_dns_resolver_destroy(void)
-{
-}
-#else
-extern int nfs_dns_resolver_init(void);
-extern void nfs_dns_resolver_destroy(void);
-#endif
-

```

```
extern ssize_t nfs_dns_resolve_name(char *name, size_t namelen,
- struct sockaddr *sa, size_t salen);
+ struct sockaddr *sa, size_t salen, struct vfsmount *rpcmount);
```

```
#endif
```

```
diff --git a/fs/nfs/inode.c b/fs/nfs/inode.c
```

```
index ce00b70..414570b 100644
```

```
--- a/fs/nfs/inode.c
```

```
+++ b/fs/nfs/inode.c
```

```
@@ -1535,10 +1535,6 @@ static int __init init_nfs_fs(void)
```

```
    err = nfs_idmap_init();
    if (err < 0)
-   goto out9;
-
-   err = nfs_dns_resolver_init();
-   if (err < 0)
        goto out8;
```

```
    err = nfs_fscache_register();
@@ -1599,10 +1595,8 @@ out5:
out6:
    nfs_fscache_unregister();
out7:
-   nfs_dns_resolver_destroy();
-out8:
    nfs_idmap_quit();
-out9:
+out8:
    return err;
}
```

```
@@ -1614,7 +1608,6 @@ static void __exit exit_nfs_fs(void)
```

```
    nfs_destroy_inodecache();
    nfs_destroy_nfspagecache();
    nfs_fscache_unregister();
-   nfs_dns_resolver_destroy();
    nfs_idmap_quit();
#ifdef CONFIG_PROC_FS
    rpc_proc_unregister("nfs");
```

```
diff --git a/fs/nfs/nfs4namespace.c b/fs/nfs/nfs4namespace.c
```

```
index 3c2a172..7a61fdb 100644
```

```
--- a/fs/nfs/nfs4namespace.c
```

```
+++ b/fs/nfs/nfs4namespace.c
```

```
@@ -14,6 +14,7 @@
```

```
#include <linux/slab.h>
```

```
#include <linux/string.h>
```

```
#include <linux/sunrpc/clnt.h>
```

```

+#include <linux/sunrpc/rpc_pipe_fs.h>
#include <linux/vfs.h>
#include <linux/inet.h>
#include "internal.h"
@@ -104,7 +105,8 @@ static size_t nfs_parse_server_name(char *string, size_t len,

    ret = rpc_pton(string, len, sa, salen);
    if (ret == 0) {
-   ret = nfs_dns_resolve_name(string, len, sa, salen);
+   ret = nfs_dns_resolve_name(string, len, sa, salen,
+   init_rpc_pipefs);
    if (ret < 0)
        ret = 0;
    }
--
1.7.3.4

```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
