
Subject: [PATCH v3, RESEND 12/16] sunrpc: introduce get_rpc_pipefs()
Posted by [Kirill A. Shutemov](#) on Tue, 08 Feb 2011 18:42:03 GMT
[View Forum Message](#) <> [Reply to Message](#)

Get rpc_pipefs mount point by path. If path is NULL, we use first
rpc_pipefs from mount table visible from current root directory.

Signed-off-by: Kirill A. Shutemov <kas@openvz.org>
Reviewed-by: Rob Landley <rlandley@parallels.com>

```
include/linux/sunrpc/rpc_pipe_fs.h | 1 +
net/sunrpc/rpc_pipe.c               | 51 +++++
2 files changed, 52 insertions(+), 0 deletions(-)
```

```
diff --git a/include/linux/sunrpc/rpc_pipe_fs.h b/include/linux/sunrpc/rpc_pipe_fs.h
index f5216f1..4a8830a 100644
--- a/include/linux/sunrpc/rpc_pipe_fs.h
+++ b/include/linux/sunrpc/rpc_pipe_fs.h
@@ -46,6 +46,7 @@ @@ RPC_I(struct inode *inode)
```

```
extern struct vfsmount *init_rpc_pipefs;
```

```
+extern struct vfsmount *get_rpc_pipefs(const char *path);
extern int rpc_pipefs_add_destroy_cb(struct super_block *sb,
    void (*destroy_cb)(void *data), void *data);
```

```
diff --git a/net/sunrpc/rpc_pipe.c b/net/sunrpc/rpc_pipe.c
index 58312fa..1261f27 100644
```

```
--- a/net/sunrpc/rpc_pipe.c
+++ b/net/sunrpc/rpc_pipe.c
@@ -16,6 +16,9 @@
#include <linux/namei.h>
#include <linux/fsnotify.h>
#include <linux/kernel.h>
+#include <linux/nsproxy.h>
+#include <linux/mnt_namespace.h>
+#include <linux/fs_struct.h>
```

```
#include <asm/ioctls.h>
```

```
#include <linux/fs.h>
```

```
@@ -939,6 +942,54 @@ static const struct super_operations s_ops = {
```

```
#define RPCAUTH_GSSMAGIC 0x67596969
```

```
+static int check_rpc_pipefs(struct vfsmount *mnt, void *arg)
+{
+ struct vfsmount **rpcmount = arg;
+ struct path path = {
```

```

+ .mnt = mnt,
+ .dentry = mnt->mnt_root,
+ };
+
+ if (!mnt->mnt_sb)
+ return 0;
+ if (mnt->mnt_sb->s_magic != RPCAUTH_GSSMAGIC)
+ return 0;
+
+ if (!path_is_under(&path, &current->fs->root))
+ return 0;
+
+ *rpcmount = mntget(mnt);
+ return 1;
+}
+
+struct vfsmount *get_rpc_pipefs(const char *p)
+{
+ int error;
+ struct vfsmount *rpcmount = ERR_PTR(-EINVAL);
+ struct path path;
+
+ if (!p) {
+ iterate_mounts(check_rpc_pipefs, &rpcmount,
+ current->nsproxy->mnt_ns->root);
+
+ if (IS_ERR(rpcmount) && (current->nsproxy->mnt_ns ==
+ init_task.nsproxy->mnt_ns))
+ return mntget(init_rpc_pipefs);
+
+ return rpcmount;
+ }
+
+ error = kern_path(p, LOOKUP_FOLLOW | LOOKUP_DIRECTORY, &path);
+ if (error)
+ return ERR_PTR(error);
+
+ check_rpc_pipefs(path.mnt, &rpcmount);
+ path_put(&path);
+
+ return rpcmount;
+}
+EXPORT_SYMBOL_GPL(get_rpc_pipefs);
+
+struct destroy_cb {
+ struct list_head list;
+ void (*callback)(void *data);
+};

```

1.7.4

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
