

---

Subject: Right use of Hostname and Name  
Posted by [Sebastian Bachmann](#) on Sun, 03 Jul 2011 11:26:33 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

-----BEGIN PGP SIGNED MESSAGE-----

Hash: SHA1

Hello,

We have some servers with some more OpenVZs installed. All running  
Debian lenny, squeeze and lenny bpo.

Now we have some troubles with the Hostname and FQDN of some VZ's. In  
the config files of all VZs is the HOSTNAME set to the FQDN. The NAME is  
set to the Hostname of the host.

In some hosts we can now see, that /etc/hostname is the FQDN, in some  
not. In the VZ's where in the /etc/hostname is the hostname, \$(hostname  
- -f) gives the FQDN... So i think some hosts have some problems with the  
hostname and the real FQDN...

So what is the right usage of HOSTNAME and NAME in the VZ conf? where i  
should use the FQDN and where just the hostname?

thanks!

sebastian

-----BEGIN PGP SIGNATURE-----

Version: GnuPG/MacGPG2 v2.0.14 (Darwin)

Comment: Using GnuPG with Mozilla - <http://enigmail.mozdev.org/>

iQEeBAEBAgAGBQJOEFHpAAoJEAhgHfpCPcybQg8H/jQIz7280XJXSRgg5jmA RWaT  
1DDPtA2fc9P1FedtEyKAU37zR8PwuwDyBNA1CQGqY6Wvi+oCGY0zqhTl8+7 Q+F3  
qbbXVINtrxFY115hO9O1/Ixt/R0zDF22APbVeyvFNRKHS6IFLDHSAp39Y34 fuXa  
FbqyVfDyq+dnnn+MBVi8pIHxXOMMPJ+x5pbYsOufHJDrbDVCeU6FuUaOf4vn dFuo  
NQuwq7bfoza18nBND8VksbCwD8iHLCW8p4vWhbQlmwvPGwF8baVCP9IABL9L zdcN  
oABN9SH5IIPRRmtzzWeYG+14d42pE8WI7DahOAfu6duNcKMhWHrdSBbCK7+O G/s=  
=h403

-----END PGP SIGNATURE-----

---