

---

Subject: Re: [PATCH] Reduce Load in VZs - stop cron.d thundering herd...

Posted by &lt;me on Wed, 03 Aug 2011 08:33:54 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

awesome thanks, i'll try it. So best is i copy all the stuff from cron.daily to cron.d and add 0 0 \* \* \* ar @daily at the beginning, or is it the same to leave them there and these things will allready called by cron?

On Wed, 03 Aug 2011 09:29:32 +0100, Tim Small <tim@seoss.co.uk> wrote:

> On 03/08/11 08:47, Kir Kolyshkin wrote:

>>

>> (3) CT has a distro installed which has crontab in some unusual location

>

> Nearly (3)

>

> /etc/cron.d is a standard location, but vps-postcreate.sh didn't deal > with it.

>

> I thought I'd submitted this patch to debian, but I seem to have dropped > it :-(

>

> Tim.

>

> --- postcreate.sh.old 2010-09-14 06:07:31.000000000 +0100

> +++ /etc/vz/dists/scripts/postcreate.sh 2011-08-03 09:27:22.490356610 +0100

> @@ -24,12 +24,12 @@

>

> function randcrontab()

> {

> - file=\${VE\_ROOT}"/etc/crontab"

> + for file in \${VE\_ROOT}/etc/cron.d/\* \${VE\_ROOT}/etc/crontab

> + do

> + [ -f "\${file}" ] || return 0

>

> - [ -f "\${file}" ] || return 0

> -

> - /bin/cp -fp \${file} \${file}.\$\$

> - cat \${file} | awk '

> + /bin/cp -fp \${file} \${file}.\$\$

> + cat \${file} | awk '

> BEGIN { srand(); }

> {

> if (\$0 ~ /^[ \t]\*#/ || \$0 ~ /^[ \t]+\*\$/) {

> @@ -61,8 +61,9 @@

> }

> print line;

```
> }
> -' > ${file}.$$ && /bin/mv -f ${file}.$$ ${file}
> -      /bin/rm -f ${file}.$$ 2>/dev/null
> +      ' > ${file}.$$ && /bin/mv -f ${file}.$$ ${file}
> +      /bin/rm -f ${file}.$$ 2>/dev/null
> +      done
> }
>
> function disableroot()
```

---