
Subject: [PATCH 3/4] add initlog feature to manual page
Posted by [dietmar](#) on Tue, 20 Sep 2011 05:17:17 GMT
[View Forum Message](#) <> [Reply to Message](#)

From: Dietmar Maurer <dietmar@proxmox.com>

Signed-off-by: Dietmar Maurer <dietmar@proxmox.com>

man/ctid.conf.5 | 5 +++++
1 files changed, 5 insertions(+), 0 deletions(-)

diff --git a/man/ctid.conf.5 b/man/ctid.conf.5

index d3ec3d0..ecda4ae 100644

--- a/man/ctid.conf.5

+++ b/man/ctid.conf.5

@@ -30,6 +30,11 @@ Specifies whether this container will be started during system boot.

Default is \fBno\fR, meaning the container will not be started

if \fBONBOOT\fR parameter is omitted.

Corresponds to the \fB--onboot\fR option.

+.IP \fBINITLOG\fR="\fByes\fR|\fBno\fR"

+If enabled init output is logged to /var/log/init.log. An additional process started

+inside the container (init-logger) reads the output from init and writes it

+to /var/log/init.log.

+Corresponds to the \fB--initlog\fR option.

.IP \fBBOOTORDER\fR="\fInumber\fR"

Specifies the CT boot order priority. Corresponds to the

\fB--bootorder\fR option.

--

1.5.6.5
