

---

Subject: [PATCH v7 8/8] Disable task moving when using kernel memory accounting

Posted by [Glauber Costa](#) on Thu, 13 Oct 2011 13:09:42 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Since this code is still experimental, we are leaving the exact details of how to move tasks between cgroups when kernel memory accounting is used as future work.

For now, we simply disallow movement if there are any pending accounted memory.

Signed-off-by: Glauber Costa <glommer@parallels.com>

Reviewed-by: KAMEZAWA Hiroyuki <kamezawa.hiroyu@jp.fujitsu.com>

---

mm/memcontrol.c | 31 ++++++-----  
1 files changed, 18 insertions(+), 13 deletions(-)

diff --git a/mm/memcontrol.c b/mm/memcontrol.c

index 1ba318d..b46232b 100644

--- a/mm/memcontrol.c

+++ b/mm/memcontrol.c

@@ -408,23 +408,11 @@ void sock\_update\_memcg(struct sock \*sk)

```
    rcu_read_lock();
    sk->sk_cgrp = mem_cgroup_from_task(current);
-
- /*
-  * We don't need to protect against anything task-related, because
-  * we are basically stuck with the sock pointer that won't change,
-  * even if the task that originated the socket changes cgroups.
-  *
-  * What we do have to guarantee, is that the chain leading us to
-  * the top level won't change under our noses. Incrementing the
-  * reference count via cgroup_exclude_rmdir guarantees that.
-  */
- cgroup_exclude_rmdir(mem_cgroup_css(sk->sk_cgrp));
    rcu_read_unlock();
}
```

void sock\_release\_memcg(struct sock \*sk)

```
{
- cgroup_release_and_wakeup_rmdir(mem_cgroup_css(sk->sk_cgrp));
}
```

void memcg\_sockets\_allocated\_dec(struct mem\_cgroup \*memcg, struct proto \*prot)

```
@@ -5634,10 +5622,17 @@ static int mem_cgroup_can_attach(struct cgroup_subsys *ss,
{
```

```

int ret = 0;
struct mem_cgroup *mem = mem_cgroup_from_cont(cgroup);
+ struct mem_cgroup *from = mem_cgroup_from_task(p);
+
+ if (from != mem &&
+     res_counter_read_u64(&mem->tcp.tcp_memory_allocated, RES_USAGE)) {
+     printk(KERN_WARNING "Can't move tasks between cgroups: "
+         "Kernel memory held. task: %s\n", p->comm);
+     return 1;
+ }

if (mem->move_charge_at_immigrate) {
    struct mm_struct *mm;
- struct mem_cgroup *from = mem_cgroup_from_task(p);

    VM_BUG_ON(from == mem);

@@ -5805,6 +5800,16 @@ static int mem_cgroup_can_attach(struct cgroup_subsys *ss,
    struct cgroup *cgroup,
    struct task_struct *p)
{
+ struct mem_cgroup *mem = mem_cgroup_from_cont(cgroup);
+ struct mem_cgroup *from = mem_cgroup_from_task(p);
+
+ if (from != mem &&
+     res_counter_read_u64(&mem->tcp.tcp_memory_allocated, RES_USAGE)) {
+     printk(KERN_WARNING "Can't move tasks between cgroups: "
+         "Kernel memory held. task: %s\n", p->comm);
+     return 1;
+ }
+
    return 0;
}
static void mem_cgroup_cancel_attach(struct cgroup_subsys *ss,
--
1.7.6.4

```

---