
Subject: [PATCH v6 7/8] SUNRPC: remove rpcbind clients creation during service registering

Posted by [Stanislav Kinsbursky](#) on Tue, 25 Oct 2011 10:17:47 GMT

[View Forum Message](#) <> [Reply to Message](#)

We don't need this code since rpcbind clients are creating during RPC service creation.

Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>

net/sunrpc/rpcb_clnt.c | 9 -----
1 files changed, 0 insertions(+), 9 deletions(-)

diff --git a/net/sunrpc/rpcb_clnt.c b/net/sunrpc/rpcb_clnt.c

index dba2331..088e4e2 100644

--- a/net/sunrpc/rpcb_clnt.c

+++ b/net/sunrpc/rpcb_clnt.c

@@ -432,11 +432,6 @@ int rpcb_register(u32 prog, u32 vers, int prot, unsigned short port)

struct rpc_message msg = {
 .rpc_argp = &map,
};

- int error;

-

- error = rpcb_create_local();

- if (error)

- return error;

dprintk("RPC: %sregistering (%u, %u, %d, %u) with local "

"rpcbind\n", (port ? "" : "un"),

@@ -572,11 +567,7 @@ int rpcb_v4_register(const u32 program, const u32 version,

struct rpc_message msg = {
 .rpc_argp = &map,
};

- int error;

- error = rpcb_create_local();

- if (error)

- return error;

if (rpcb_local_clnt4 == NULL)

return -EPROTONOSUPPORT;
