Subject: [PATCH v6 7/8] SUNRPC: remove rpcbind clients creation during service registering
Posted by Stanislav Kinsbursky on Tue, 25 Oct 2011 10:17:47 GMT
View Forum Message <> Reply to Message

We don't need this code since rpcbind clients are creating during RPC service
creation.

Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>

---
 net/sunrpc/rpcb_clnt.c | 9 ---------
 1 files changed, 0 insertions(+), 9 deletions(-)

```
diff --git a/net/sunrpc/rpcb_clnt.c b/net/sunrpc/rpcb_clnt.c
index dba2331..088e4e2 100644
--- a/net/sunrpc/rpcb_clnt.c
+++ b/net/sunrpc/rpcb_clnt.c
@@ -432,11 +432,6 @@ int rpcb_register(u32 prog, u32 vers, int prot, unsigned short port)
  struct rpc_message msg = {
   .rpc_argp = &map,
  };
- int error;
-
- error = rpcb_create_local();
- if (error)
-  return error;

  dprintk("RPC:       %sregistering (%u, %u, %d, %u) with local "
    "rpcbind\n", (port ? "" : "un"),
@@ -572,11 +567,7 @@ int rpcb_v4_register(const u32 program, const u32 version,
  struct rpc_message msg = {
   .rpc_argp = &map,
  };
- int error;

- error = rpcb_create_local();
- if (error)
-  return error;
  if (rpcb_local_clnt4 == NULL)
   return -EPROTONOSUPPORT;
```