

---

Subject: [PATCH v7 6/7] SUNRPC: remove rpcbind clients creation during service registering

Posted by [Stanislav Kinsbursky](#) on Fri, 28 Oct 2011 10:54:34 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

We don't need this code since rpcbind clients are creating during RPC service creation.

Signed-off-by: Stanislav Kinsbursky <[skinsbursky@parallels.com](mailto:skinsbursky@parallels.com)>

---

net/sunrpc/rpcb\_clnt.c | 9 -----  
1 files changed, 0 insertions(+), 9 deletions(-)

diff --git a/net/sunrpc/rpcb\_clnt.c b/net/sunrpc/rpcb\_clnt.c

index c144b95..115c691 100644

--- a/net/sunrpc/rpcb\_clnt.c

+++ b/net/sunrpc/rpcb\_clnt.c

@@ -431,11 +431,6 @@ int rpcb\_register(u32 prog, u32 vers, int prot, unsigned short port)

struct rpc\_message msg = {  
    .rpc\_argp = &map,  
};

- int error;

-

- error = rpcb\_create\_local();

- if (error)

- return error;

dprintk("RPC:     %sregistering (%u, %u, %d, %u) with local "

"rpcbind\n", (port ? "" : "un"),

@@ -571,11 +566,7 @@ int rpcb\_v4\_register(const u32 program, const u32 version,

struct rpc\_message msg = {  
    .rpc\_argp = &map,  
};

- int error;

- error = rpcb\_create\_local();

- if (error)

- return error;

if (rpcb\_local\_clnt4 == NULL)

return -EPROTONOSUPPORT;

---