

---

Subject: [PATCH v4 2/3] SUNRPC: optimize net\_ns dereferencing in rpcbind creation calls

Posted by [Stanislav Kinsbursky](#) on Tue, 08 Nov 2011 10:43:17 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Static rpcbind creation functions can be parametrized by network namespace pointer, calculated only once, instead of using init\_net pointer (or taking it from current when virtualization will be completed) in many places.

Signed-off-by: Stanislav Kinsbursky <[skinsbursky@parallels.com](mailto:skinsbursky@parallels.com)>

---

```
net/sunrpc/rpcb_clnt.c | 35 ++++++-----
1 files changed, 19 insertions(+), 16 deletions(-)
```

```
diff --git a/net/sunrpc/rpcb_clnt.c b/net/sunrpc/rpcb_clnt.c
```

```
index 7d32f19..3df276a 100644
```

```
--- a/net/sunrpc/rpcb_clnt.c
```

```
+++ b/net/sunrpc/rpcb_clnt.c
```

```
@@ -161,10 +161,10 @@ static void rpcb_map_release(void *data)
    kfree(map);
}
```

```
-static int rpcb_get_local(void)
```

```
+static int rpcb_get_local(struct net *net)
```

```
{
    int cnt;
```

```
- struct sunrpc_net *sn = net_generic(&init_net, sunrpc_net_id);
```

```
+ struct sunrpc_net *sn = net_generic(net, sunrpc_net_id);
```

```
    spin_lock(&sn->rpcb_clnt_lock);
```

```
    if (sn->rpcb_users)
```

```
@@ -201,9 +201,10 @@ void rpcb_put_local(void)
```

```
}
}
```

```
-static void rpcb_set_local(struct rpc_clnt *clnt, struct rpc_clnt *clnt4)
```

```
+static void rpcb_set_local(struct net *net, struct rpc_clnt *clnt,
```

```
+ struct rpc_clnt *clnt4)
```

```
{
```

```
- struct sunrpc_net *sn = net_generic(&init_net, sunrpc_net_id);
```

```
+ struct sunrpc_net *sn = net_generic(net, sunrpc_net_id);
```

```
    /* Protected by rpcb_create_local_mutex */
```

```
    sn->rpcb_local_clnt = clnt;
```

```
@@ -211,22 +212,23 @@ static void rpcb_set_local(struct rpc_clnt *clnt, struct rpc_clnt *clnt4)
```

```
    smp_wmb();
```

```
    sn->rpcb_users = 1;
```

```

dprintk("RPC:    created new rpcb local clients (rpcb_local_clnt: "
- "%p, rpcb_local_clnt4: %p)\n", sn->rpcb_local_clnt,
- sn->rpcb_local_clnt4);
+ "%p, rpcb_local_clnt4: %p) for net %p%s\n",
+ sn->rpcb_local_clnt, sn->rpcb_local_clnt4,
+ net, (net == &init_net) ? " (init_net)" : "");
}

/*
 * Returns zero on success, otherwise a negative errno value
 * is returned.
 */
-static int rpcb_create_local_unix(void)
+static int rpcb_create_local_unix(struct net *net)
{
    static const struct sockaddr_un rpcb_localaddr_rpcbind = {
        .sun_family = AF_LOCAL,
        .sun_path = RPCBIND_SOCK_PATHNAME,
    };
    struct rpc_create_args args = {
- .net = &init_net,
+ .net = net,
        .protocol = XPRT_TRANSPORT_LOCAL,
        .address = (struct sockaddr *)&rpcb_localaddr_rpcbind,
        .addrsz = sizeof(rpcb_localaddr_rpcbind),
@@ -259,7 +261,7 @@ static int rpcb_create_local_unix(void)
        clnt4 = NULL;
    }

- rpcb_set_local(clnt, clnt4);
+ rpcb_set_local(net, clnt, clnt4);

out:
    return result;
@@ -269,7 +271,7 @@ out:
 * Returns zero on success, otherwise a negative errno value
 * is returned.
 */
-static int rpcb_create_local_net(void)
+static int rpcb_create_local_net(struct net *net)
{
    static const struct sockaddr_in rpcb_inaddr_loopback = {
        .sin_family = AF_INET,
@@ -277,7 +279,7 @@ static int rpcb_create_local_net(void)
        .sin_port = htons(RPCBIND_PORT),
    };
    struct rpc_create_args args = {
- .net = &init_net,

```

```
+ .net = net,  
  .protocol = XPRT_TRANSPORT_TCP,  
  .address = (struct sockaddr *)&rpcb_inaddr_loopback,  
  .addrsz = sizeof(rpcb_inaddr_loopback),  
@@ -311,7 +313,7 @@ static int rpcb_create_local_net(void)  
  clnt4 = NULL;  
}
```

```
- rpcb_set_local(clnt, clnt4);  
+ rpcb_set_local(net, clnt, clnt4);
```

out:

```
  return result;  
@@ -325,16 +327,17 @@ int rpcb_create_local(void)  
{  
  static DEFINE_MUTEX(rpcb_create_local_mutex);  
  int result = 0;  
+ struct net *net = &init_net;
```

```
- if (rpcb_get_local())  
+ if (rpcb_get_local(net))  
  return result;
```

```
  mutex_lock(&rpcb_create_local_mutex);  
- if (rpcb_get_local())  
+ if (rpcb_get_local(net))  
  goto out;
```

```
- if (rpcb_create_local_unix() != 0)  
- result = rpcb_create_local_net();  
+ if (rpcb_create_local_unix(net) != 0)  
+ result = rpcb_create_local_net(net);
```

out:

```
  mutex_unlock(&rpcb_create_local_mutex);
```

---