

---

Subject: [PATCH] SUNRPC: destroy freshly allocated transport in case of sockaddr init error

Posted by [Stanislav Kinsbursky](#) on Thu, 10 Nov 2011 10:36:27 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Otherwise we will leak xprt structure and struct net reference.

Signed-off-by: Stanislav Kinsbursky <[skinsbursky@parallels.com](mailto:skinsbursky@parallels.com)>

---

net/sunrpc/xprtsock.c | 4 +++-

1 files changed, 3 insertions(+), 1 deletions(-)

diff --git a/net/sunrpc/xprtsock.c b/net/sunrpc/xprtsock.c

index d7f97ef..2d78d95 100644

--- a/net/sunrpc/xprtsock.c

+++ b/net/sunrpc/xprtsock.c

@@ -2530,8 +2530,10 @@ static struct rpc\_xprt \*xs\_setup\_xprt(struct xprt\_create \*args,  
int err;

err = xs\_init\_anyaddr(args->dstaddr->sa\_family,  
(struct sockaddr \*)&new->srcaddr);

- if (err != 0)

+ if (err != 0) {

+ xprt\_free(xprt);

return ERR\_PTR(err);

+ }

}

return xprt;

---