
Subject: [PATCH 4/7] perf: teach "perf inject" to work with files
Posted by [Andrew Vagin](#) on Mon, 28 Nov 2011 09:03:32 GMT
[View Forum Message](#) <> [Reply to Message](#)

Before this patch "perf inject" can only handle data from pipe.

I want to use "perf inject" for reworking events. Look at my following patch.

Signed-off-by: Andrew Vagin <avagin@openvz.org>

tools/perf/builtin-inject.c | 33 ++++++
1 files changed, 31 insertions(+), 2 deletions(-)

diff --git a/tools/perf/builtin-inject.c b/tools/perf/builtin-inject.c

index 8dfc12b..8df8b71 100644

--- a/tools/perf/builtin-inject.c

+++ b/tools/perf/builtin-inject.c

@@ -13,7 +13,12 @@

#include "util/parse-options.h"

-static char const *input_name = "-";

+static char const *input_name = "-";

+static const char *output_name = "-";

+static int pipe_output = 0;

+static int output;

+static u64 bytes_written = 0;

+

static bool inject_build_ids;

static int perf_event__repipe_synth(union perf_event *event,

@@ -25,12 +30,14 @@ static int perf_event__repipe_synth(union perf_event *event,
size = event->header.size;

while (size) {

- int ret = write(STDOUT_FILENO, buf, size);

+ int ret = write(output, buf, size);

if (ret < 0)

return -errno;

size -= ret;

buf += ret;

+

+ bytes_written += ret;

}

return 0;

@@ -213,8 +220,14 @@ static int __cmd_inject(void)

```

if (session == NULL)
    return -ENOMEM;

+ if (!pipe_output)
+ lseek(output, session->header.data_offset, SEEK_SET);
    ret = perf_session__process_events(session, &inject_ops);

+ if (!pipe_output) {
+ session->header.data_size += bytes_written;
+ perf_session__write_header(session, session->evlist, output, true);
+ }
    perf_session__delete(session);

    return ret;
@@ -228,6 +241,10 @@ static const char * const report_usage[] = {
static const struct option options[] = {
    OPT_BOOLEAN('b', "build-ids", &inject_build_ids,
        "Inject build-ids into the output stream"),
+ OPT_STRING('i', "input", &input_name, "file",
+     "input file name"),
+ OPT_STRING('o', "output", &output_name, "file",
+     "output file name"),
    OPT_INCR('v', "verbose", &verbose,
        "be more verbose (show build ids, etc)"),
    OPT_END()
@@ -243,6 +260,18 @@ int cmd_inject(int argc, const char **argv, const char *prefix __used)
if (argc)
    usage_with_options(report_usage, options);

+ if (!strcmp(output_name, "-")) {
+ pipe_output = 1;
+ output = STDOUT_FILENO;
+ } else {
+ output = open(output_name, O_CREAT | O_WRONLY | O_TRUNC,
+     S_IRUSR | S_IWUSR);
+ if (output < 0) {
+ perror("failed to create output file");
+ exit(-1);
+ }
+ }
+
    if (symbol__init() < 0)
        return -1;

--
1.7.1

```
