

---

Subject: Re: [PATCH 4/5] NFS: remove RPC PipeFS mount point reference from blocklayout routines

Posted by [Myklebust, Trond](#) on Tue, 29 Nov 2011 17:19:25 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

On Tue, 2011-11-29 at 11:42 -0500, J. Bruce Fields wrote:

> On Tue, Nov 29, 2011 at 11:40:30AM -0500, Trond Myklebust wrote:

> > I mean that I'm perfectly entitled to do

> >

> > 'modprobe -r blocklayoutdriver'

> >

> > and when I do that, then I expect blkmapd to close the rpc pipe and wait

> > for a new one to be created just like rpc.idmapd and rpc.gssd do when I

> > remove the nfs and sunrpc modules.

>

> The rpc pipefs mount doesn't hold a reference on the sunrpc module?

I stand corrected: the mount does hold a reference to the sunrpc module.

However nothing holds a reference to the blocklayoutdriver module, so the main point that the "blocklayout" pipe can disappear from underneath the blkmapd stands.

--

Trond Myklebust

Linux NFS client maintainer

NetApp

[Trond.Myklebust@netapp.com](mailto:Trond.Myklebust@netapp.com)

[www.netapp.com](http://www.netapp.com)

---