
Subject: [PATCH 6/6] perf: add scripts for profiling sleep times (v2)

Posted by [Andrey Vagin](#) on Wed, 07 Dec 2011 13:56:01 GMT

[View Forum Message](#) <> [Reply to Message](#)

E.g.:

```
# perf script record -- sched:sched_stat_sleep -- ./foo
```

```
# perf script report sched-stat
```

or

```
# perf script record -- -e sched:sched_stat_sleep
```

v2: Add ability to record events for a defined process. It executes a small bash script, then executes perf with filtering by pid and then a bash script executes a target process.

Signed-off-by: Andrew Vagin <avagin@openvz.org>

```
tools/perf/scripts/python/bin/sched-stat-record | 65 ++++++
```

```
tools/perf/scripts/python/bin/sched-stat-report | 5 ++
```

```
2 files changed, 70 insertions(+), 0 deletions(-)
```

```
create mode 100644 tools/perf/scripts/python/bin/sched-stat-record
```

```
create mode 100644 tools/perf/scripts/python/bin/sched-stat-report
```

```
diff --git a/tools/perf/scripts/python/bin/sched-stat-record
```

```
b/tools/perf/scripts/python/bin/sched-stat-record
```

```
new file mode 100644
```

```
index 0000000..02da7c1
```

```
--- /dev/null
```

```
+++ b/tools/perf/scripts/python/bin/sched-stat-record
```

```
@@ -0,0 +1,65 @@
```

```
#!/bin/bash
```

```
## perf script record -- sched:sched_stat_[smth] -- CMD
```

```
## perf script record -- -e sched:sched_stat_[smth]
```

```
##
```

```
+set -o monitor
```

```
+
```

```
+usage()
```

```
+{
```

```
+ echo "Usage:"
```

```
+ echo " perf script record sched-stat -- sched:sched_stat_[smth] -- CMD"
```

```
+ echo " perf script record sched-stat -- [PERF_OPTS] -e sched:sched_stat_[smth]"
```

```
+ exit 1;
```

```
+}
```

```
+
```

```
+declare -a opt
```

```
+declare -a cmd
```

```
+f=0;
```

```
+for i in "${@:2}"; do
```

```
+ if [ "$i" == "--" ]; then
```

```

+ f=1
+ continue
+ fi
+ if [ $f -eq 1 ]; then
+ cmd[${#cmd[*]}]="$i"
+ else
+ opt[${#opt[*]}]="$i"
+ fi
+done
+
+if [[ "${opt[@]}" != *sched_stat_* ]]; then
+ usage;
+fi
+
+if [ ${#cmd[@]} -eq 0 ]; then
+ if [ ${#opt[@]} -eq 0 ]; then
+ usage;
+ fi
+ exec perf record -agP \
+ -e sched:sched_switch \
+ --filter "prev_state == 1 || prev_state == 2" \
+ "${opt[@]}"
+fi
+
+if [ ${#opt[@]} -ne 1 ]; then
+ usage;
+fi
+
+## Wait until a target process is stopped.
+bash -c 'kill -STOP $$; exec "$@" -- "${cmd[@]}" &
+pid=$!
+wait %1
+[ $? -eq 147 ] || exit 1;
+
+perf record -agP \
+ -e sched:sched_switch \
+ --filter "prev_pid == $pid && prev_state == 1 || prev_state == 2" \
+ -e sched:sched_process_exit -e "${opt[@]}" --filter "pid == $pid" &
+pid_perf=$!
+kill -CONT %1
+while ;; do
+ wait %1
+ [ $? -eq 127 ] && break;
+done
+kill -INT %2
+wait %2
diff --git a/tools/perf/scripts/python/bin/sched-stat-report
b/tools/perf/scripts/python/bin/sched-stat-report

```

```
new file mode 100644
index 0000000..e5114ce
--- /dev/null
+++ b/tools/perf/scripts/python/bin/sched-stat-report
@@ -0,0 +1,5 @@
+#!/bin/bash
+# description: profiling sleep times
+perf inject -s -i perf.data -o perf.data.d || exit
+perf report -i perf.data.d || exit
+unlink perf.data.d
--
1.7.1
```
