
Subject: Re: [PATCH 1/4] SUNRPC: use passed network namespace context in
rpc_parse_scope_id()

Posted by [Stanislav Kinsbursky](#) on Mon, 12 Dec 2011 16:18:05 GMT

[View Forum Message](#) <> [Reply to Message](#)

> On Mon, Dec 12, 2011 at 08:03:45PM +0400, Stanislav Kinsbursky wrote:

>>> On Wed, Dec 07, 2011 at 03:20:16PM +0300, Stanislav Kinsbursky wrote:

>>>> Use incoming network context in rpc_parse_scope_id() instead of hard-coded

>>>>

>>>> Changelogs are a little confusing; I might have said "allow

>>>> rpc_parse_scope_id() caller to pass in network context instead of using

>>>> hard-code "init_net".

>>>>

>>>> Probably, your variant is better. My English is not good enough to

>>>> write descriptive and, in the same time, clear and short comments to

>>>> patches.

>>>>

>>>> Uh, and mine's got a problem or two as well. ("hard-code" should be

>>>> "hard-coded" in the above.)

>>>>

>>>> My main complaint was just that "incoming network context" sounds like

>>>> it refers to the network context associated with an incoming rpc

>>>> request. But actually all you're doing is using the network context

>>>> passed in by the caller.

>>>>

>>>> --b.

Yep, agreed.

I'll resend next patch set version with better comments.

--

Best regards,

Stanislav Kinsbursky
